

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved by
Budget Bureau
6. LEASE DESIGNATION

NM 05791

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. WELL TYPE OIL ☐ GAS ☒ WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME -
2. NAME OF OPERATOR Sinclair Oil & Gas Company		8. FARM OR LEASE NAME Graham "B" WN Federal
3. ADDRESS OF OPERATOR 501 Lincoln Tower Bldg., 1860 Lincoln St., Denver, Colo.		9. WELL NO. 5
4. LOCATION OF WELL - Report location clearly and in accordance with any State requirements.* (See also space 17 below.) At surface: Unit letter "W" 1000' r/South & 1790' r/West lines Section 4-27N-8W		10. FIELD AND POOL OR SURVEY OR AREA So. Elmore Pictured Cliffs
11. SEC., T., R., M., OR B.L. SURVEY OR AREA Section 4-27N-8W		12. COUNTY OR PARISH San Juan
14. PERMIT NO. Mr. J.L. Ward, 3/22/66	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6735' G.L.	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	REPAIR OR ALTER CASING
FRACTURE TREATMENT	RECOMPLETION COMPLETE
SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS
OTHER:	


WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other) Setting casing	X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR CONTINGENT OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to T.D. 7150', Ran I-ES & GR-Density logs. Logs indicated non-productive in Mesaverde and Dakota formations. Spotted 33 sack cement plugs 7250-7350', 5250-5350' and 4550-4650'. Spotted 38 sack cement, 2% CaCl plug 3500-3600'. WOC. Checked top plug @ 3520'. Ran 98 jts 4-1/2" OD 9.5" casing set @ 3191', ground mass., with 200 ex 50-50 Class "C" and Dia-Mix "A" (264 cu ft.), preceded w/ E-J GR-100 wash, pop plug to 5154', plug down 2 p.m. 4/14/66. WOC.

Prep to perforate Pictured Cliffs, treat if necessary, and complete in P.C..



18. I hereby certify that the foregoing is true and correct

SIGNED N. E. Brown TITLE Chief Office Clerk DATE 4/18/66

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: