

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SE 078384

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

NEWSON #8

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

BASIN DAKOTA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASEC. 17, T-26-N, R-8-W,
N.M.P.M.

12. COUNTY OR PARISH

SAN JUAN

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☐ WELL GAS ☒ WELL OTHER

2. NAME OF OPERATOR

SOUTHERN UNION PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 808, FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1835 FT. FROM NORTH LINE AND 1780 FT. FROM EAST LINE.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6350 FT. RKB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) SUPPLEMENTARY HISTORY

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

1. DRILLED 7-7/8" HOLE TO T.D. OF 6750 FT. RKB. T.D. NOVEMBER 2, 1966.
2. RAN 213 JTS. OF 4-1/2" 10.50#, J-55 Csg. LANDER @6745 RKB. CEMENT 1ST STAGE @6600 FT. OF 50-50 POZNIX CLASS "C" CEMENT W/2% GEL, 6-1/4" GILSONITE/SX., 5% SALT/SX. AND 1/4" CFR 2. PLUG DOWN 12:05 P.M., 11/4/66. CEMENT 2ND STAGE @4703' RKB W/750 CU. FT. OF 50-50 POZNIX CLASS "C" W/8% GEL., 1/4" FLO-GELE/SX. PLUG DOWN 12:50 P.M. 11/4/66. CEMENT THIRD STAGE THRU STAGE COLLAR @2236' W/1050 CU.FT. OF 50-50 POZNIX CLASS "C" W/8% GEL., 1/4" FLO-GELE/SX. PLUG DOWN 2:00 P.M.
3. RIGGED UP COMPLETION UNIT NOVEMBER 15, 1966.
4. RAN 1-1/2" EUE TSG. DRILLED STAGE COLLARS @2236' & 4703'. CLEANED OUT TO P.B.T.D. OF 6710 R.K.B.
5. TESTED CASING W/3500 PSI FOR 15 MIN. TESTED OK. NOVEMBER 16, 1966
6. RAN GAMMA-RAY CORRELATION LOG AND CEMENT BOND LOG.
7. PERFORATED 1ST STAGE DAKOTA 2 SPE 6612 - 6617, 6635-6639, 6646-6650, 6664-6676 FT. SAND WATER FRAC 2/10,000# 40-60 SAND AND 25,000# 20-40 SAND W/50,330 GAL OF 8% KCL WATER W/20#/1000 WA-B.
8. SET 4-1/2" BRIDGE PLUG @6570' RKB.
9. PERFORATE 2ND STAGE DAKOTA W/2 SPF 6526-6554. SAND WATER FRAC W/35,000# 20-40 SAND, 15,000# 10-20 SAND, 500# 12-20 GLASS BEADS AND 49,490 GAL. OF 0.8% KCL WATER W/4# FR-8/1000 GAL.
10. RAN 1-1/2" EUE TSG. DRILLED BRIDGE PLUG @6570 RKB. CLEANED OUT TO P.B.T.D. OF 6710 RKB.
11. RAN 201 JTS AND PERF JT. OF 1-1/2" UEU, 2.90# JCN TUBING.
12. COMPLETED WELL NOVEMBER 17, 1966.

18. I hereby certify that the foregoing is true and correct
Original signed by
GILBERT D. NOLAND, JR.

SIGNED

GILBERT D. NOLAND, JR.

TITLE DRILLING SUPERINTENDENT

DATE

NOVEMBER 23, 1966

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

NOV 25 1966

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional offices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for special instructions.

Item 5: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.