BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)					SF/	SF 078431 6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
					8. xF 17			
OIL CAS WELL WELL	X OTHER				7. UNIZ	AGREEMENT P	NAME	
2. NAME OF OPERATOR	OTHER	· · · · · · · · · · · · · · · · · · ·		/ 1		4 00 12:02		
Consolidated Oil & Gas, Inc.					1	8. FARM OR LEASE NAME CON HALE		
3. ADDRESS OF OPERATOR						9. WHLL NO.		
P.O. Box 20	38, Farn	nington, Ne	w Mexico	87499 [°]		3		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990 * FNL & 790 * FEL						10. FIELD AND POOL, OR WILDCAT Bacin DK/Ballard PC		
						26. T2	6N, R8W	
14. PERMIT NO.		15. ELEVATIONS (Sh		•	12. con	NTY OR PARIS	H 13. STATE	
		1 690	8 CR OF L		San	Juan	N.M.	
16.	Check A	ppropriate Box To	Indicate Na	ture of Notice, Report, o	or Other Da	ta		
NOTICE OF INTENTION TO						UENT REPORT OF:		
TEST WATER SHUT-	OFF	PULL OR ALTER CASING	c	WATER SHUT-OFF	_	REPAIRING	WELL .	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING C	11	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING		ABANDONME	NT* X	
EEPAIR WELL (Other)	<u></u>	CHANGE PLANS		(Other)	mite of multin	· · · · · · · · · · · · · · · · · · ·		
•	OR COMPLETED OPE	PATIONS (C)early stat	n all partings.	(Note: Report res Completion or Rec	ompletion Repo	ort and Log fo	on Well rm.)	
proposed work. I nent to this work.)	f well is direction	onally drilled, give su	bsurface location	details, and give pertinent de is and measured and true ve	stes, including rtical depths f	estimated dat or all marker	te of starting any s and zones perti-	
5-7-84 Ins	stall BOP	. Pulled 8	34 jts 1	-1/2" tubing.				
5-8-84 Dri	lled bri	dge plug at	2893'.	Drilled out	bridges	at 489	4'-4980',	
50J	.3', 5795	c hole clea	JU5 '- 615	8'. Drilled ha	ard ceme	ent fro	m 6094'-	
				Cl"B" w/ 2% Ca	C1 \			
, , , , , , , , ,	Spot 18	cu ft plus	over G	allun 6006-506/	(1 2) •			
Per	Spot 18 cu ft plug over Gallup 6096-5964' $^{\prime\prime}$ Perf 2 shots at 4300'. Set 5-1/2" packer at 3 $^{\prime\prime}$					3965'. Squeeze		
Mes	esa Verde w/ 84 cu ft cmt. Top of cement at					4034'.		
	Spot 36 cu ft over Pictured Cliffs perfs 28					26201.		
				and 2510-2378'.				
				amo 2008-1876!				
	Spot 10	ted coment	suriace	e shoe 410-278' ' to surface.	' •			
Nir	pled dow	n BOP & rig	r down	to surface.	P (2) 6	ា ទា ស ស) F29 F255	
		er & cleane		cation.				
			- up 20	3401011.	M			
					MA'	Y 2 3 1984	4	
						CON. E	W	
						-) i V .	
					ı	DIST. 3		
8. I hereby certify that	the foregoing is	true and correct						
SIGNED Lac	bara E		ITLE Prod.	& Drlg. Technic	ian DAT	5-15	-84	
(This space for Fede	ral or State office				DA1			
APPROVED BYCONDITIONS OF AI		T:	ITLE		rad	re		

NMOCC

*See Instructions on Reverse Side