



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 070001
Unit San Juan

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 1, 1950

Well No. 127(10) is located 990 ft. from N line and 1350 ft. from E line of sec. 25

NE/4 SW/4 25 (1/4 Sec. and Sec. No.) 25 N (Twp.) 10 W (Range) S.M.P.M. (Meridian)

Angel Peak, Del Norte Co. (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 2235 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 9-29-50, Total Depth 1510'.
Ran 157 joints 7", 23 #, 1510' - 11-30, 9:22' - J-55
set at 1032'. Two stage cementing tool at 2450'. First
stage 170 sacks regular cement, w/0.4 BR-L, 4 % gal and 1/4 #
Flocculants, 1/4 # 200 # Pmg/ak., followed w/50 aks. Best cement
w/0.4 BR-L.
Second stage 80 aks. regular cement, w/2 % calcium chloride.
Hold 100' 30 minutes.
Top of cement by temperature survey on second stage at 1070'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 970

Farmington, New Mexico

By W. C. Helm

Title Petroleum Engineer