


COPY FOR  
STATE OF NEW MEXICO  
OIL CONSERVATION  
COMMISSION  
SUBMIT IN TRIPLICATE TO  
DISTRICT OFFICE

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_

Lease No. \_\_\_\_\_

Unit \_\_\_\_\_



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF STOPPING OR RESUMING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	X
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Parliament, New Mexico, Lat 1, 1952

Well No. 2 is located 290 ft. from N line and 333 ft. from W line of sec. 10

N 1/4 of section 10  
(1/4 Sec. and Sec. No.)

1-76-1-10  
(Twp.) (Range)

10 N  
(Mending)

Wildcat  
(Field)

San Juan  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 6716 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddling jobs, cementing points, and all other important proposed work)

Well was drilled to a total depth of 2365 feet and plugged back to a total depth of 2380 feet in December, 1927. 5-1/2" casing was set at 2275 feet with 500 sacks of cement. The well made 50 MCF per day natural test and 250 MCF per day after being shot with 70 parts of 160 from 2310 to 2380 feet and cleaned out to 2380 feet. Well was shut in until March, 1932.

Table tool riser was moved onto well March 1, 1932. Well was pulled down and cleaned out to 2380 feet. A caliper survey indicated that 5-1/2" casing was set at 2274 feet.

Well was plugged back with pea gravel from 2380 feet to 2465 feet and was shot with 216 parts of 160 from 2365 feet to 2385 feet with gravel cap from 2385 feet to 2465 feet and oil-seal cap from 2465 feet to 2475 feet. Not perforated at 1:59 A.M., on

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Co. New Mexico

Address Box 487  
Parliament, New Mexico

By H. C. Sperry  
Title Production Foreman

March 23, 1952. Well was cleaned out to 2364 feet. On water test well measured 7 gallons of water per hour. Pitot tube test measured 186 MCF per day. 1-1/4" tubing was landed at 2331 feet. Well was shut in 72 hours. Shut in casing pressure was 384 psi. Well measured 214 MCF per day after 2 hour blow down through 2" casing outlet with pitot tube through 2" pipe nipple April 8, 1952. Well was shut in.