

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

Water Source Well* (P&A)

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FNL - 1650' FEL
Sec. 35, T26N, R13W, NMPM

5. Lease Designation and Serial No.

SF 078155

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

West Bisti Unit

8. Well Name and No.

West Bisti Unit 149

9. API Well No.

30-045-95006

10. Field and Pool, or Exploratory Area

*Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Tag @ 1813' with tubing.
2. Perforate Pictured Cliffs @ 1370'.
3. Run tubing to 1383'. Spot 388 cu.ft. Class B + 4% gel cement.
4. Pull tubing. Run fullbore packer. Displace cement to 936'. No flow back. Pictured Cliffs - Fruitland plug 936' - 1383'.
5. Perforate below surface casing at 100'.
6. Run packer to 31'. Fill casing and annular space with 107 cu. ft. Class B + 4% gel cement. Packer. Top off casing with cement. Surface plug 0' - 100'.

Job complete 6-11-93.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander

Title

Operations Manager

Date

6/14/93

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

APPROVED

JUN 17 1993

DISTRICT MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

BLM/COO