

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR
Reading & Bates Petroleum Co.
3. ADDRESS OF OPERATOR
3200 Mid-Continent Tower Tulsa, OK 74103
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980'FNL & 1980'FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

5696'KB

5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-5019

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NAVAJO INDIAN

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

NAVAJO TOCITO

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Tocito Dome

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 9-T26N-R18W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Procedure to P&A

1. Set CIBP @ 6272'.
2. Set 50' cement plug on CIBP from 6222'-6272'.
3. Shoot squeeze holes & set plug from 5395'-5495'.
4. Shoot squeeze holes & set plug from 3672'-3772'.
5. Shoot squeeze holes & set plug from 2733'-2833'.
6. Shoot squeeze holes & set plug from 1555'-1655'.
7. Shoot squeeze holes & set plug from 1070'-1170'.
8. Shoot squeeze holes & set plug from 715'-815'.
9. Shoot squeeze holes & set plug from 156'-surface.
10. Cement annulus between 8-5/8" & 13-3/8".

9.2# mud or greater between plugs.

DEC 23

OIL CONTROL
DIST. 3

APPROVED

18. I hereby certify that the foregoing is true and correct

SIGNED

Math C. Frihart

TITLE

Engineer Technician

DATE

12-15-87

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side