

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SE 078433

6. IF INDIAN, ABBOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

NEWSON

9. WELL NO.

20

10. FIELD AND POOL, OR WILDCAT

BASIN DAKOTA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 19, T-26N, R-8W,

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

SAN JUAN

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

SOUTHERN UNION PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 808, FARMINGTON, NEW MEXICO 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

970 FT. FROM THE NORTH LINE AND 990 FT. FROM THE EAST
LINE.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6257 FT. R.K.B.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spudding


REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

1. SPUDDED 12-1/4" SURFACE HOLE ON FEBRUARY 27, 1968. DRILLED TO TOTAL DEPTH OF 330 FT. R.K.B.
2. RAN 10 JOINTS 8-5/8", 24.0#, J-55 SURFACE CASING. LANDED AT 314 FT. R.K.B. CEMENTED W/200 SACKS REGULAR CEMENT W/2% CALCIUM CHLORIDE AND 1/4# GEL-FLAKE PER SACK. PLUG DOWN 2:00 A.M. FEBRUARY 28, 1968. CEMENT CIRCULATED TO SURFACE.
3. NIPPLED UP AND PRESSURE TESTED SURFACE CASING AND BLOWOUT PREVENTOR TO 1000 PSI FOR 15 MINUTES. TEST OK.
4. DRILLED OUT FROM UNDER SURFACE CASING WITH 7-7/8" HOLE ON FEBRUARY 28, 1968.



RECEIVED

MAR 3 1968

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

18. I hereby certify that the foregoing is true and correct

Original signed by

SIGNED GILBERT D. NOLAND, JR.

GILBERT D. NOLAND, JR.

(This space for Federal or State office use)

TITLE DRILLING SUPERINTENDENT

DATE MARCH 8, 1968

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

987-881

