

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

RM 01368

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Barfano Unit

8. FARM OR LEASE NAME

Barfano Unit

9. WELL NO.

174

10. FIELD AND POOL, OR WILDCAT

Barfano Unit
11. SEC., T., R., OR NE. AND
SURVEY OR AREA

Sec. 13, T-26-N, R-10-W

12. COUNTY OR PARISH 18. STATE

Santa Fe

New Mexico

1. OIL ☐ GAS ☐ OTHER ☒
WELL WELL

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 990, Farmington, New Mexico - 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650'N, 990'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6574' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☒

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 3-23-68 spudded well, drilled surface hole and ran 7 joints 8 5/8", 24#, J-55 casing (218') set at 228' w/195 sacks of cement circulated to surface. W.O.C. 12 hours, tested w/600#/30 Min. O. K.

On 4-6-68 T.D. 6889'. Ran 214 joints 4 1/2", 10.5#, J-55 casing (6879') set at 6889'. Float collar set at 6883', second stage at 4913', third stage at 2338'. Cemented first stage w/270 sks. cement, second stage w/150 sks. cement, third stage w/170 sks. cement. W.O.C. 18 hours.

On 4-7-68 P.B.T.D. 6866', tested casing to 4000' O. K. Spotted 300 gal. 1 1/2% regular acid. Perf. 6610-20', 6634-39', 6692-6707', 6760-70', 6790-95', 6826-31' w/20 SVZ. Free w/65,000# 40/60 sand, 68,040 gal. water. Max. pr. 4000#, BEP 2800#, tr. pr. 3600-3800-4000#. I.R. 31.2 BPM. Dropped 5 sets of 24 balls each. Balled off on fifth ball drop. Shut down.



RECEIVED

APR 10 1968

U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED Original signed by
Carl E. Matthews

TITLE **Petroleum Engineer**

DATE **4-8-68**

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

887-851

