Form 3160-5 November 1983) Formerly 9-331)	UNITED S	TATES THE INTERIO	SUBMIT IN TRIPLICATE (Other Instructions on reverse side)	I EXPITES AUGUST 31 TORS
<u> </u>	BUREAU OF LAND			5. LEASE DESIGNATION AND SERIAL NO. SF 078571
(Do not use th	NDRY NOTICES AND is form for proposals to drill or to use "APPLICATION FOR PER	REPORTS ON deepen or plus for such in	WELLS Werent reservoir.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS WELL	OTHER	U	ENED	7. UMIT AGREEMENT NAME
El Paso I	<u>Natural Gas Com</u> pa	inv Ou	AUG 1 3 1984 U	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATO	OR	- OIL	CON. DIV	Day B 9. WBLL NO.
4. LOCATION OF WELL (See also space 17 be At surface	-	cordance with any Sta	te requirements.	10. FIELD AND POOL, OR WILDCAT
	1700'S, 1616'W	<u></u>		Basin Dakota 11. SEC. T. R. M., OR ELE. AND SURVEY OF AREA Sec. 7, 1-27-N, R- NMPM
14. PERMIT NO.	4. PERMIT NO. 18. ELEVATIONS (Show whether DF, ET, GR, etc.)			
16.		6745 °C		San Juan NM
14.	Check Appropriate Box	To Indicate Nati	re of Notice, Report, or C	Other Data
	MOTICE OF INTENTION TO:			THAT REPORT OF:
TEST WATER SHUT-	I TO ALIEN C	· —	WATER SHUT-OFF	REPAIRING WELL X
SHOOT OR ACIDIZE	MULTIPLE COMPIL	ETTE	FRACTURE TREATMENT	ALTERING CARING
REPAIR WELL	ABANDON®		SHOOTING OR ACIDIZING	ABANDONMENT*
(Other)	CHANGE PLINS		(Other)	of multiple completion on Well
17. DESCRIBE PROPOSED O	E COMPLETED OPERATIONS (Clearly	State all pertinent de	Completion or Recompl	etion Report and Log form.)
nent to this work.			•	etion Report and Log form.) Including estimated date of starting and depths for all markers and sonce percentage of the starting and sonce percentage of the starting and sonce percentage of the starting and sonce percent
7-12-84		on and rigg	ged up. Pulled	tubing.
7 - 13 - 84	Isolated casing	failures a	it 347' to 378'.	and 5077' to 5107'.
5 4 4 4 4	Squeeze cemente	d leak at 9	5077' with 47 cu	.ft. cement. WOC
7-14-84	Found new leak	from 567' t	to 598'. Squeez	e cemented with
	4/ cu.it. cemen	t. WOC 4 hi	s. Squeeze cem	ented leak from 347'
	to 3/8' with 24	cu.tt. cen	ent. WOC 18 hr	S

tested casing to 800 psi, ok. Ran 229 jts. 2 3/8", 4.7#, tubing stung into cement retainer set at 7191'. Loaded tubing - casing annulus with corrosion inhibitor.

18. I hereby certify that the foregoing is true and correct signed Drilling Clerk

TITLE DATE 8-2-84

CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE 1984

53 cu.ft. cement. WOC.

WOC.

cement.

7-16-84

7-17-84

7-18-84

7-18-84

Drilled out cement to 600', pressure tested casing, did not hold. Isolated leak from 347' to 378'. Squeeze cemented with

Drilled out cement, pressure tested top two leaks to 800 psi,

Drilled out lower squeeze cement. Pressure tested casing, did not hold. Squeeze cemented from 5077' to 5107' with 53 cu.ft.

Tagged cement at 4795'. Drilled out squeeze cement. Pressure

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA