Form 3160-5 November 1983) Formerly 9-331)

## UNITED STATES SUBMIT IN TRIPLICATE\* Other instructions on reverse side)

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SF 078571

	BURLAU OF LAI	NAMAGEMENT				
SUNDRY NOTICES AND REPORTS ON WELLS 100 Not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)				6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
:	OIL GAS OTHER P&A		88 DEC 19 AMII: 22	7. UNIT AGREEMENT NA	ME	
2.	NAME OF OPERATOR Union Oil Company of Califor	nia	- AMERICA OF SOURCE AT	8. FARM OR LEASE NAM	IE .	
<u>.</u> –	ADDRESS OF OPERATOR		FARMINGTON, NEW MEN	WELL NO.		
	P. O. Box 2620 - Casper, WY				3	
1.	LOCATION OF WELL (Report location clearly and it See also space 17 below.) At surface	accordance with any Sta	respression of the	NO. FIELD AND POOL, OF		
	801' FNL & 11	90' FEL	DEGS S 1300	Basin Dakota 11. SEC., T., E., M., OR BLE. AND SURVEY OR AREA		
				Sec. 7, T.2	7N., R.8W.	
14.		rions (Show whether DF, RT,	GR. e(C)	12. COUNTY OR PARISH	1	
	API No. 30-045-20151	6246' GR		San Juan	New Mexico	
6.	Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data					
	NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
	TEST WATER SHUT-OFF PULL OR ALT	ER CASING	WATER SHUT-OFF	REPAIRING W	WELL	
	FRACTUBE TREAT MULTIPLE CO	MPLETE	FRACTURE TREATMENT	ALTERING CA	<del></del>	
	SHOOT OR ACIDIZE ABANDON®	i <del></del> !	SHOOTING OR ACIDIZING	ABANDONMEN	'T*   <u>^</u>	
	REPAIR WELL CHANGE PLAN		(Other) (Norm: Report results Completion or Recomple	of multiple completion of the street of the	on Well	
7.	DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.)					
<u>Plugged and Abandoned Subject Well as Follows:</u> MIRU well service unit on 12-9-88. N.D. tree. N.U. BOP and tested to 1500 psi O.K. Stung out of retainer at 6749'. Circulated hole with 9 ppg mud. Spotte						
					00 psi,	
					Spotted	
	70 sacks of class "H" cement with 2% gel (14.8 ppg; yield 1.18 cu. ft./yd) from 6749-5701' (Plug No. 1). P.U. to 4670'. Spotted 100 sacks of class "H" cement with 2% gel from 4670-3173' (Plug No. 2). P.U. to 2420'. Spotted 93 sacks of class "H" cement with 2% gel from 2420-1225' (Plug No. 3). P.U. to 1225' and					
	circulated hole clean. Recovered 5 bbls. cement at surface.) Tagged firm cement at 1300'. Perforated from 1175-1176' with 4" casing gun with 4 jspf. RIH with					
	at 1300'. Perforated from 1175-1176' with 4" casing gun with 4 jspf. RIH with 4-1/2" cement retainer on 2-3/8" tubing, setting retainer at 1075'. Stung into					
	retainer and established injection rate of 1/2 bpm at 1500 psi. Pumped 105 sacks					
	of class "H" cement with 2% gel through retainer at 1075' and circulated cement to surface up 4-1/2" $\times$ 8-5/8" annulus. Stung out of retainer. Spotted 10 sacks					
	of cement on top of retainer from 1075-960' (Plug No. 4). P.U. to 280'. Spotted					
	22 sacks of class "H" cement with 2% get from 280' to surface (Plug No. 5). N.D. BOP. Cut off 8-5/8" and 4-1/2" casing 4' below ground level and installed dry hole marker. Cleaned up location. Released rig at 2:30 p.m, 12-10-88. Well plugged and abandoned on 12-10-88.					
F. 1990 and abandoned on 12 10 00.						
	Note: A sundry notice will final inspection.	i be submitted	as soon as the $10^{-3}$	ocation is rea	idy for	
(S.	I hereby certify that the topogoing if true aprice	appet //		· · · · · · · · · · · · · · · · · · ·		
•	SIGNED JOHN R. Under ha	Ullana Dis	trict Drilling Supt.		13-88	
	(This space for Federal or State office use)					
	APPROVED BY	TITLE		DA\$***		
	OONDITIONS OF APPROVAL, IF ANY:		19500 L	So' 5/1 -	WIT .	
			James	C, Zawa	aug.	
	and the second s	*See Instructions on	Reverse Side	MENTODOS A PARTO DO		
				,		