

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

RECEIVED  
BLM

Sundry Notices and Reports on Wells

94 JUL 20 AM 10:53

1. Type of Well  
GAS

2. Name of Operator  
MERIDIAN OIL

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M.  
800' FSL, 1150' FWL, Sec. 21, T-26-N, R-10-W, NMPM, San Juan County

API # (assigned by OCD)

5. Lease Number

6. State Oil & Gas Lease Fee

7. Lease Name/Unit Name

Huerfano Unit

8. Well No.  
196

9. Pool Name or Wildcat  
Basin Dakota

10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☒ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

7-14-94 MIRU. ND master valve, NU BOP. TOH w/209 jts 2 3/8" tbg.

7-15-94 TIH w/4 1/2" scraper, tag fill @ 6669'. TOH. TIH w/Baker 4 1/2" RBP & FB pkr, set RBP @ 6392'. PT RBP to 1000 psi. Dump one sx sd on RBP. Isolate csg leak @ 169-174'. TOH. Pressured up csg to 1000 psi & holding. TIH w/pkr & set @ 74'. PT down tbg to 1000 psi, no leak, LD pkr. RU, run GR-CBL-CCL @ 0-2350'. TOC @ 670'. Shot 2 sqz holes @ 630'. RD. Load well w/30 bbl wtr.

7-16-94 RU. TIH w/pkr, set @ 385'. PT backside of pkr to 500 psi, leaked off. Pull pkr & reset @ 169'. Backside held OK. TOH. TIH, pump 190 sx Class "B" neat cmt w/2% calcium chloride, cmt to surface. Circ 5 bbl cmt to pit. Final sqz pressure 100 psi. WOC. SDON.

7-17-94 TIH w/3 7/8" drag bit & 3 1/8" drill collars, tag cmt @ 79'. Drill out cmt @ 79-195'. Test csg to 750 psi, OK. Drill cmt to 630'. PT csg to 750 psi, lost 200 psi in 5 min. TOH. TIH w/4 1/2" scraper to 900'. TOH. TIH w/4 1/2" Baker FB pkr, set @ 322'. TOH. RU, pump 50 sx Class "B" neat cmt w/2% calcium chloride. Release pkr. TOH w/pkr, pressure to 1000 psi. SDON.

7-18-94 TIH w/3 7/8" bit & 3 1/8" drill collars. Drill cmt to 635'. PT csg to 750 psi, kist 39 psi/15 min. TOH. TIH w/4 1/2" scraper & retrieving tool. Circ sd off top of plug & release plug. TOH. SDON.

7-19-94 Blow well & CO. Ran 209 jts 2 3/8" 4.7# J-55 8RDEUE tbg, set @ 6612'. ND BOP, NU Master Valve. RD. Rig released 5:30 p.m. 7-18-94.

SIGNATURE

Regulatory Affairs July 19, 1994

(This space for State Use)

Approved by

DEPUTY OIL & GAS INSPECTOR, DIST. #3

Title

Date JUL 28 1994