

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
E-9707

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	West Bisti Unit
3. Address of Operator	8. Field or Lease Name
Box 670, Hobbs, New Mexico 88240	9. Well No.
4. Location of Well	10. Field and Pool, or Wellbore
UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM	Bisti Lower Gallup
THE West LINE, SECTION 36 TOWNSHIP 26-N RANGE 13-W N.M.P.M.	
11. Elevation (Show whether DF, RT, GR, etc.)	12. County
6217' GL	San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:


SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPER. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

13. I submit (report or) Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4886' TD, 4884' PB.

Cactus Drilling Company reached TD of 7-7/8" hole at 4886' at 5:40 PM, June 5, 1969. Ran 151 joints, 4875' of 5-1/2" 15.5# K-55 ST&C casing set and cemented at 4885' with 100 sacks of Class C with 16% gel, 2% salt and 100 sacks of Class C neat. Bump plug with 1500#. TS indicated top of cement at 3400'. WOC & NU 18 hours. Drilled float at 4851' and 32' of cement to 4884' plug back depth.



14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY	TITLE	DATE
C. D. BORLAND	Area Production Manager	June 9, 1969
APPROVED BY	TITLE	DATE
<i>[Signature]</i>	SUPERVISOR DIST. 3	JUN 12 1969
CONDITIONS OF APPROVAL, IF ANY:		