STATE OF NEW MEXICO
ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

OIL CONSERVATION DIVISION

RECEIVED
JUN 11 1987
OIL CON. DIV.
DIST. 3

Page 1
Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator R. C. WYNN Lease FEDERAL J Well No. # 1 (CM)

Location of Well: Unit B Sec. 11 Twp. 27 Rge. 8 County San Juan

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. or Csg.)
Upper Completion	CHACRA	GAS	FLOW	TBG.
Lower Completion	MESA VERDE	GAS	FLOW	TBG.

PRE-FLOW SHUT-IN PRESSURE DATA

	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)
Upper Completion	4-19-87	3-Days	0	Yes
Lower Completion	4-19-87	3-Days	0	Yes

FLOW TEST NO. 1

Commenced at (hour, date)* 4-22-87 Zone producing (Upper or Lower): Lower

Time (hour, date)	Lapsed Time (hours)	Pressure: Upper Completion	Pressure: Lower Completion	Prod. Zone Temp.	Remarks
4-20-87	1-Day	0	0		Both Zones Shut In
4-21-87	2-Days	0	0		Both Zones Shut In
4-22-87	3-Days	0	0		Both Zones Shut In
4-23-87	1-Day	0	0		Lower Zone Flowing
4-24-87	2-Days	0	0		Lower Zone Flowing

duction rate during test

: _____ BOPD based on _____ Bbls. in _____ Hours. _____ Grav. _____ GOR _____

: 0 MCFPD; Tested thru (Orifice or Meter): Meter

MID-TEST SHUT-IN PRESSURE DATA

	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)
Upper Completion				
Lower Completion				

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

FLOW TEST NO. 2

Commenced at (hour, date)** _____

Zone producing (Upper or Lower): _____

TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE Upper Completion	PRESSURE Lower Completion	PROD. ZONE TEMP.	REMARKS

Production rate during test

Oil: _____ BOPD based on _____ Bbls. in _____ Hours. _____ Grav. _____ GOR _____

Gas: _____ MCFPD: Tested thru (Orifice or Meter): _____

Remarks: BOTH ZONES ON THE WELL ARE DEAD

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

Approved JUN 11 1987, 19___ — Operator R. C. WYNN

New Mexico Oil Conservation Division — By Robert Chanault

Original Signed by CHARLES GHOLSON — Title _____

By DEPUTY OIL & GAS INSPECTOR, DIST. #3 — Date 5-3-87

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

A packer leakage test shall be commenced on each multiply completed well within thirty days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.

A packer leakage test shall commence when both zones of the dual completion are shut in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.

For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be conducted for a minimum period of seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

Flow Test No. 2 shall be conducted even though no leakage may have been indicated during the first flow test. Flow Test No. 2 shall be conducted with the zone which was previously shut-in while the zone which was previously flowed shall remain shut-in.

Pressure for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least once each day during each flow period (at approximately the same time) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).