

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

070 SAN JUAN, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

BLEDSON PETRO CORPORATION

214/742-5800

3. Address and Telephone No.

1717 MAIN STREET SUITE 5850 DALLAS TX 75201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

)- T.27 N. R.8 W. SEC. 11
790' FNL & 1450' FEL

5. Lease Designation and Serial No.

NMSF-078476

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

UNIT B

8. Well Name and No.

FEDERAL J 1

9. API Well No.

10. Field and Pool, or Exploratory Area

BLANCO MESAVERDE

11. County or Parish, State

SAN JUAN, NEW MEXICO

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TOP OF NACIMIENTO 1130'
TOP OF OJO ALAMO 2081'
TOP OF KIRTLAND 2201'
TOP OF FRUITLAND 2741'
TOP OF PICTURED CLIFFS 2952'
TOP OF LEWIS 3070'
TOP OF CHACRA 3874'
TOP OF CLIFF HOUSE 4620'
TOP OF MENEFE 4647'
TOP OF POINT LOOKOUT 5215'
TOP OF MANCOS 5393'



PLEASE SEE ATTACHED
FOR PROCEDURES

to PBTD

14. I hereby certify that the foregoing is true and correct

Signed

(This space for Federal or State office use)

Title

PETROLEUM ENGINEER

Date

2/16/96

Approved by

Conditions of approval, if any:

Title

APPROVED

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instructions on Reverse Side

BLEDSON PETRO CORPORATION
PLUGGING PROCEDURES
FEDERAL J 1

- 1) Set CIBP @ 4570' and spot 50' of cement on top of plug
- 2) Perf @ 3924', place cement plug from 3924' to 3824' inside and outside the casing with 100% excess cement in the annulus and an additional 50 linear feet inside the casing.
- 3) Perf @ 2791', place cement plug from 2791' to 2691' inside and outside the casing with 100% excess in the annulus and an additional 50 linear feet inside the casing.
- 4) Perf @ 2251', place cement plug from 2251' to 2031' inside and outside the casing with 100% excess in the annulus with and 50 linear feet inside the casing.
- 5) Perf @ 1180', place cement plug from 1180' to 1080' inside and outside the casing with 100% excess in the annulus with and 50 linear feet inside the casing.
- 6) Perf @ 221' and circulate cement to surface.