

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Conoco, Inc.

3. Address and Telephone No.

10 Desta Dr. Ste 100W, Midland, TX 79705 (915) 686-6548

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

790' FNL & 990' FEL  
Sec. 11, T-27N, R-8W

5. Lease Designation and Serial No.

SE  
082078476

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Oxnard

8. Well Name and No.

1

9. API Well No.

30-045-20630

10. Field and Pool, or Exploratory Area

So. Blanco P.C.

11. County or Parish, State

San Juan

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion or well completion or recompletion report and log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well will be P&A'd according to the attached procedure.

RECEIVED  
MAY 30 1995  
OIL CON. DIV.  
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed

*[Signature]*

Title

Sr. Conservation Coordinator

Date

5/19/95

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

NMOCD

DISTRICT MANAGER

# Oxnard #1

Current

South Blanco Pictured Cliffs

NE Section 11, T-27-N, R-8-W, San Juan County, NM

OJO PARTNERSHIP, INC.

Today's Date: 3/31/95

Spud: 4/24/70

Completed: 6/5/70

12-1/4" hole

8-5/8" 24# J-55 Csg set @ 105'  
Cmt w/85 sxs (Circulated to Surface)

Nacimiento @ 1008'

Ojo Alamo @ 2177'

Top of Cmt @ 2102'  
(Calc, 75%)

Kirtland @ 2209'

Fruitland @ 2702'

Pictured Cliffs @ 2966'

Pictured Cliffs Perforations:  
2970' - 78", 2998' - 3012'

94 jts 1-1/4" 2.4# JCW EUE tubing set @ 2985'

PBTD 3025'

6-3/4" Hole

TD 3074'

4-1/2" 9.5# K-55 set @ 3074'  
179 cf cement

## PLUG & ABANDONMENT PROCEDURE

3-31-95

Oxnard #1  
So. Blanco Pictured Cliffs  
NE Section 11, T-27-N, R-8-W  
San Juan County, New Mexico

**Note:** All cement volumes use 100% excess outside pipe and 50' excess inside pipe. The stabilizing wellbore fluid will be 8.3 ppg, sufficient to balance all exposed formation pressures.

1. Install and test location rig anchors. Prepare blow pit. Comply to all NMOCD, BLM, and Conoco safety regulations.
2. MOL and RU daylight pulling unit. Conduct safety meeting for all personnel on location. NU relief line. Blow down well and kill with water as necessary. ND wellhead and NU BOP. Test BOP.
3. POH and tally 94 joints 1-1/4" EUE tubing (2985'). Visually inspect, if necessary LD and PU 2" tubing workstring.
4. **Plug #1 (Pictured Cliffs perforations and Fruitland top, 3025' - 2652'):** RIH with open ended tubing to 3025' or as deep as possible. Pump 25 bbls water down tubing. Mix 51 sxs Class B cement (50% excess, long plug) from 3025' to 2652' to cover Pictured Cliffs perms and Fruitland top. POH to 1800' and WOC. RIH and tag cement. Load well with water and circulate clean. Pressure test casing to 500#. POH to 2259'.
5. **Plug #2 (Kirtland and Ojo Alamo tops, 2259' - 2127'):** Mix 15 sxs Class B cement and spot a balanced plug from 2259' to 2127' inside 4-1/2" casing to cover Kirtland and Ojo Alamo tops. POH with tubing and LD setting tool. Pressure test casing to 500#.
6. **Plug #3 (Nacimiento, 1058' - 958'):** Perforate 4 squeeze holes at 1058'. Establish rate into squeeze holes if casing tested. PU 4-1/2" cement retainer and RIH; set at 1008', pressure test tubing to 1000#, establish rate into Nacimiento squeeze holes. Mix 36 sxs Class B cement, squeeze 24 sxs cement outside 4-1/2" casing from 1058' to 958' and leave 12 sxs cement inside casing to cover Nacimiento top. POH and LD tubing.
7. **Plug #4 (Surface):** Perforate 2 squeeze holes at 155'. Establish circulation out bradenhead valve. Mix and pump 44 sxs Class B cement from 155' to surface, circulate good cement out bradenhead valve. Shut in well and WOC.
8. ND BOP and cut off wellhead below surface casing. Install P&A marker with cement to comply with regulations. RD, MOL, cut off anchors, and restore location.

# Oxnard #1

Proposed P &  
South Blanco Pictured Cliffs

NE Section 11, T-27-N, R-8-W, San Juan County, NM

Today's Date: 3/31/95  
Spud: 4/24/70  
Completed: 6/5/70

12-1/4" hole

8-5/8" 24# J-55 Csg set @ 105'  
Cmt w/85 sxs (Circulated to Surface)

Perforate @ 155'

Plug #4 155' - Surface with  
45 sxs Class B cement.

Nacimiento @ 1008'

Cement Rt @ 1008'

Plug #3 1058' - 958' with  
36 sxs cement, 24 sxs  
outside and 12 sxs inside.

Perforate @ 1058'

Ojo Alamo @ 2177'

Top of Cmt @ 2102'  
(Calc, 75%)

Plug #2 2259' - 2127' with  
15 sxs Class B cement.

Kirtland @ 2209'

Fruitland @ 2702'

Plug #1 3025' - 2652' with  
51 sxs Class B cement,  
(50% excess, long plug).

Pictured Cliffs @ 2966'

Pictured Cliffs Perforations:  
2970' - 78', 2998' - 3012'

6-3/4" Hole

RTD 3025'

TD 3074'

4-1/2" 9.5# K-55 set @ 3074'  
179 cf cement