

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078384

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Starr

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Ballard P. C.

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 6, T26N, R8W NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

N. M.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Austral Oil Company Incorporated

3. ADDRESS OF OPERATOR

2700 Humble Bldg., Houston, Texas 77002

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)  
At surface

1120' fel 1190' fsl

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6148' Gr

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐

(Other) casing settings

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 11" hole to 143'. Set 4 jts., 7-5/8", 26.40# J-55 casing at 138'. Cemented w/75 sax Class A cement with 2% CaCl. Tested 7-5/8" casing &amp; BOP to 800#, OK. Circulated cement.

Drilled 6-3/4" hole to 2,106'. Set 4-1/2", 9.5#, J-55 casing at 2,095'. Cemented with 260 sax 50/50 poz 3 with 6% gel &amp; 1/4#/sax clinton flake. Tailed in with 75 sax class A plus 2% CaCl. Circulated cement.

Perforated the zone 2014 to 2016' with eight 1/2" holes.

Stimulated with 30,000 gallons Dowell Wide Frac fluid with 51,000# 20/40 sand. Tagged sand with 30 MC IR192.

Now testing well. Additional reports to follow.

RECEIVED

MAR 29 1971

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

*James King*

TITLE District Superintendent

DATE March 24, 1971

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE