

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004 0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen, or to enter to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NMNM-019401

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

UNIT M

8. Well Name and No.

LARGO FEDERAL 1

9. API Well No.

10. Field and Pool, or Exploratory Area

OTERO CHACRA *Elavio*

11. County or Parish, State

SAN JUAN, NEW MEXICO

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

BLEDSON PETRO CORPORATION

214/742-5800

3. Address and Telephone No.

1717 MAIN STREET SUITE 5850 DALLAS TX 75201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

11 - T.27 N. R.8 W. ~~SEC. 11~~  
850' FSL & 790' FWL

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form 1)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the work.)

|                        |               |
|------------------------|---------------|
| TOP OF NACIMIENTO      | 290'          |
| TOP OF OJO ALAMO       | 1340'         |
| TOP OF KIRTLAND        | 1465'         |
| TOP OF FRUITLAND       | 1996'         |
| TOP OF PICTURED CLIFFS | 2200'         |
| TOP OF LEWIS           | 2317'         |
| TOP OF CHACRA          | 3128'         |
| TOP OF CLIFF HOUSE     | 3888'         |
| TOP OF MENELEE         | 3910'         |
| TOP OF POINT LOOKOUT   | 4457'         |
| TOP OF MANCOS          | 4625' to PBTD |

PLEASE SEE ATTACHED  
FOR PROCEDURES

14. I hereby certify that the foregoing is true and correct

Signed

*[Signature]* Title PETROLEUM ENGINEER

Date

2/11/86

(This space for Federal or State Office use)

Approved by

Title

Date

Conditions of approval, if any:

APPROVED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

**BLEDSON PETRO CORPORATION**  
**PLUGGING PROCEDURES**  
**LARGO FEDERAL #1**

- 1) Set CIBP @ 3550' and spot 50' of cement on top of plug
- 2) Perf @ 3178', place cement plug from 3178' to 3078' inside and outside the casing plus 100% excess cement in the annulus and an additional 50 linear feet inside the casing.
- 3) Perf @ 2046', place cement plug from 2046' to 1946' inside and outside the casing with 100% excess in the annulus and an additional 50 linear feet inside the casing.
- 4) Perf @ 1515', place cement plug from 1515' to 1290' inside and outside the casing with 100% excess in the annulus with and 50 linear feet inside the casing.
- 5) Perf @ 340' and circulate cement to surface.