

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

STANDARDIZED INSTRUCTIONS
(Other instructions on file
version 100)

Form approved.
Budget Bureau No. 42-R1424.

4. LEASE DESIGNATION AND SERIAL NO.
14-20-603-3034

5. IF INDIAN, ALLOTTEE OR TRIBE NAME
Navajo Tribe

6. UNIT AGREEMENT NAME

7. FARM OR LEASE NAME
Navajo Tribal "U"

8. WELL NO.
13

9. FIELD AND POOL, OR WILDCAT
Tecito Dome Penn. "D"

10. SEC. T. R. M. OR BLK. AND
QUARTER OR AREA
**NW/4 SE/4 Section 16,
T-26-N, R-18-W**

11. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY

12. ADDRESS OF OPERATOR
501 Airport Drive, Farmington, New Mexico 87401

13. LOCATION OF WELL (Report location clearly and define with any State required notes.
See also space 17 below.)
At surface

1980' FSL & 1980' FSL, Unit "J"

14. PERMIT NO.

15. SITUATIONS (State whether DE, ST, LE, etc.)
5780' ungraded GL

16. COUNTY OR PARISH
San Juan

17. STATE
New Mexico

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

19. TYPE OF INTEREST TO:

20. SUBSEQUENT REPORT OF:

YES - WATER SIGNIFICANT ☐ OTHER WATER OWNERS ☐
PRACTICAL TRIAL ☐ FURTHER COMPLIANCE ☐
WELL OR ALLEGE ☐ ABANDONMENT ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other)

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FEASURE TREATMENT ☐ ALTERING CASING ☐
ABANDONING OR ACCELERATING ☐ ABANDONMENT* ☒
(Other) **Find & set casing**

(Note: Report results of multiple completion on Well Completion or Log Completion Report and Log form.)

19. Describe in detail the work and operation, including a description of the work, the date of starting any proposed work, if well is directionally drilled, give the well location and measured and true vertical depths for all markers and zones pertinent to this work.) *

A 12-1/4" surface hole was spudded 4:00 p.m., February 8, 1973, and drilled to 106'. A 17-1/4" hole opener was run to 100' and the 13-3/8" casing was set at 97' on February 9, 1973. The casing was cemented with 100 sacks Class "A" cement with 2% CaCl₂ and the cement circulated. The casing and blowout preventer were tested for 30 minutes with 650 psig oil. The hole was reduced to 12-1/4" at 100'.

The 12-1/4" hole was drilled to 1540' and a 3-1/2" water flow was encountered at 1265'. The 9-5/8" casing was set at 1536' with 400 sacks Class "C" cement with 4% Gel and 2 pounds Tuf Plug per sack and 100 sacks Class "C" Neat, February 12, 1973. The cement circulated.

FEB 15 1973

U. S. GEOLOGICAL SURVEY



20. I hereby certify that the foregoing is true and correct

SIGNED _____ Area Engineer

DATE February 12, 1973

(This space for Federal or State or use)

APPROVED BY _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands, pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. For necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of putting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.