## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	Sundry No	tices and Reports on	Wells
1. Type o	f Well GAS	:	5. Lease Number NM-03017 6. If Indian, All.or Tribe Name
2. Name of Operator The El Paso Natural Gas Company			7. Unit Agreement Name Huerfano Unit
3. Address & Phone No. of Operator Box 4289, Farmington, NM 87499 (505)326-9700			<ul><li>8. Well Name &amp; Number Huerfano Unit #234</li><li>9. API Well No.</li></ul>
4. Location 1180'S	on of Well, Footag , 1750'E Sec.7 , T	e,Sec,T,R,M. -26-N, R-9-W, NMPM	10.Field and Pool Basin Fruitland Coal 11.County and State San Juan County, NM
Type of St	PPROPRIATE BOX TO ubmission ice of Intent	Type of Abandonment _X Recompletion	OTICE, REPORT, OTHER DATA  F Action  Change of Plans  New Construction  Non-Routine Fracturing
	al Abandonment	Casing Repair Altering Casing Other	Water Shut Off
13. Descr	ibe Proposed or Co	mpleted Operations	MAR 2 9 1991
10-15-90	5650'. Open bypa circ. SDFN. Top of pkr @ 562 5610'. TOOH w/17 5602'. PT tbg 10 chaloride. Displ vis mud @ 5507'. 3848'. Set cmt re Class "B" cmt w/out of retainer.	ss. Pump wtr down the 1'. Ran freepoint local 9 jts 2 3/8" the w/20 00#, ok. Pump 75 sx 0 ace w/20 BW. Reverse LD 57 jts the TOOH. et @ 3730'. Tested be 2% calcium chloride, LD 50 jts 2 3/8" the (cont'd on back)	NU BOP. Work Stuck pkr @ g, tbg on vacuum. Unable to g to 5615'. Cut off tbg @ o' cut off. Set cmt ret @ class "B" w/2% calcium circ w/80 bbl. 9.0 ppg 50. Perf 4 squeeze holes @ ackside, failed. Pump 90 sx displace w/13 BW. Sting g. TOOH w/35 stds. SDFN.
Signed		the foregoing is true  Title Regulatory	and correct Affairs Date 10-26-90
(This space	ce for Federal or	State office use)	ACCEPTED FOR RECORD
APPROVED BYCONDITION OF APPROVAL, IF ANY:		TITLE	MARE 1 5 1991
		· · · · · · · · · · · · · · · · · · ·	FARMINGTON RESOURCE AREA

## Huerfano Unit #234, cont'd.

- PT csg 800#, ok. TIH w/logging tool, tag @ 1895'. TIH w/scraper to 2250'. Circ hole w/wtr. Ran GR-CCL-CNL. Set 4 1/2" CIBP @ 2225'. PT csg 1000#, ok. Ran CBL. TOC @ 2030'. TIH, circ hole w/2% KCl wtr. SDFN.
- 10-19-90 Spot 185 gal. 15% HCl acid @ 2206'. Pull tbg to 1850'. Swab. TOOH. Perf 2044-64', 2088-96', 2114-28', 2138-68', 2206-10'. TIH w/SPIT tool. BD perfs w/800 gal. 15% HCl acid. TOOH w/SPIT. Swabbed. SDFN.
- Swabbed. Reperf'd 2088-96' w/16 shots. TIH w/SPIT tool. BD zone w/300 gal. 15% HCl acid. Pull tbg to 2010'. Swabed. SDFN.
- 10-21-90 Swabbed. Ran 70 jts 2 3/8", 4.7#, J-55 EUE tbg set @ 2088'. SN @ 2156'. SDFN.
- 10-22-90 Swabbed. Released rig.