Form 9-331 (May 1963)	UNITED STATES	instructions on relation in the Budget Bureau No. 42-R1424.  5. LEASE DESIGNATION AND SERIAL NO.				
	DEPARTMENT OF THE INTERIOR VOISES  GEOLOGICAL SURVEY	NM 01368				
(Do not use	UNDRY NOTICES AND REPORTS ON WEL this form for proposals to drill or to deepen or plug back to a difference "APPLICATION FOR PERMIT—" for such proposals.)	Contracted on The Name  6. If Indian, Allottee on The Name  7. Unit agreement name				
El Paso 3. ADDRESS OF OPE PO Box 9	Vatural Gas Company 100, Farmington, NM 87401  L. (Report location cirarly and in accordance with any State require	Huerfano Unit 8. FARM OR LEASE NAME Huerfano Unit 9. WELL NO. 241				
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6551'G.L	NMPM 12. COUNTY OF PARISH 13. STATE San Juan New Mexico				
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:						
	WATE	REPAIRING WELL				

NOTICE OF INTENTION TO:			50B5EQUENT N22 022 02	
TEST WATER SHUT-OFF FEACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS		water shut-off  Fracture treatment shooting or acidizing  (Other)  (Note: Report results of mul Completion or Recompletion R	REPAIRING WELL ALTERING CASING ABANDONMENT*  tiple completion on Well eport and Log form.)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*
  - TD 6072'. Ran 190 joints 4 1/2", 10.5#, KS production casing, 6060' set at 6072'. 5-26-73 Float collar set at 6056' and stage tool set at 2347'. Cemented first stage with 793 cu.ft. cement, and second stage with 357 cu.ft. cement. WOC 18 hours. Topof cement at 1580'.
  - PBTD 6056'. Tested casing to 4000#-OK. Perf'd 5628', 5644,5650', 5688', 5694', 5-28-73 5728', 5766', 5781', 5787', 5846', 5852', 5900', 5906', 5950', 5968' 6006' and 6012' with one shot each. Frac'd with 100,000# 40/60 sand and 101,000 gallons treated water. No ball drops. Flushed with 4200 gallons water.

