

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

NOO-C-14-20-2622  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo  
7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Callegos  
9. WELL NO.

8  
10. FIELD AND POOL, OR WILDCAT

Basin Dakota  
11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 34 T26N R11W  
12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

Suite 1200 Lincoln Tower Bldg., Denver, Colorado 80203

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

933' FSL and 880' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6268.0' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data.

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

Spudded 12-1/4" surface hole 12:30 p.m. 9/1/73. Drilled to 623' KDB.  
Ran 19 jts. 8-5/8" 24# K-55 ST&C casing and set at 623'. Cemented  
with 420 sacks class "A" with 2% CaCl2. Circulated to surface. Plug  
down at 10:40 a.m. 9/2/73. WOC 12 hours. Tested casing to 1000 psi  
held ok. Preparing to drill out from under surface casing.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Clerk

DATE 9/14/73

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side