

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NOO-C-14-20-2727

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo Tribe "BP"

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Tocito Dome

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

35, T26N, R18W, NMPM

12. COUNTY OR PARISH 13. STATE

San Juan N. Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. WELL TYPE ☒ OIL ☒ GAS ☐ OTHER

2. NAME OF OPERATOR

TEXACO, Inc.

3. ADDRESS OF OPERATOR

P. O. Box EE, Cortez, Colorado 81321

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
(See also page 17 below.)
At surface

2130' From South Line & 510' From West Line

14. FIELD NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5593' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

1. WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

2. FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

3. SHOOTING OR ACIDIZING

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

4. PLUG WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. IF WIRE PROBE OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Abandoned this well because it was completed non-productive: 9-20-74.

Procedure:

Filled hole with mud. Spot 30 sacks cement PBTD to 6300'. Run free point
and cut casing at 3229'. Spot 50 sacks cement 100' in and out of casing stub.
Spot 75 sacks cement plugs 3900'-3700' and 2150'-1950'. Spot 70 sacks cement
1700'-1550' across intermediate casing shoe and 10 sacks cement at surface
with marker.



18. I hereby certify that the foregoing is true and correct

SIGNED W. A. M. M. M.

TITLE Field Foreman

DATE 3-26-75

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

USGS (3), OGCC (2), JAS, JHP, GLE, ARM