Form 9-331 (Mry 1963)

UNITED STATES

SUBMIT IN TRIPLIC

Form approved. Budget Bureau No. 42-R1424.

(Ma	DEPARTMENT OF THE INTERIOR Verse slo GEOLOGICAL SURVEY	instructions of	ı re-	5. LEASE DESIGNATION AND SERIAL NO. SF080893 6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
	SUNDRY NOTICES AND REPORTS ON WELL (Do not use this form for proposals to drill or to deepen or plug back to a differ Use "APPLICATION FOR PERMIT—" for such proposals.)	S						
ī."	OIL GAS OTHER			7. UNIT AGREEMENT NAME Huerfano Unit				
2.	NAME OF OPERATOR			8. FARM OR LEASE NAME Huerfano Unit				
	El Paso Natural Gas Company			9. WELL NO.				
3.	ADDRESS OF OPERATOR			1 **				
	Box 990, Farmington, New Mexico			261 10. FIELD AND FOOL, OR WILDCAT				
4.	LOCATION OF WELL (Report location clearly and in accordance with any State requirer See also space 17 below.) At surface	nents.•		Basin Dakota 11. SEC., T., B., M., OR BI SURVEY OF AREA				
	990's, 1650'W	Sec. 20, T-26-N, R-10-W						
14	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6494 GL			San Juan	New Mexic			
16.	D. T. I. I'm to Notice Papart or Other Data							
			UBSEQUENT REPORT OF:					
	TEST WATER SHUT-OFF PULL OR ALTER CASING WATER	R SHUT-OFF URE TERATMENT	X	 /	ļ			

ABANDON MENT* SHOOTING OR ACIDIZING ARANDON* SHOOT OR ACIDIZE (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) CHANGE PLANS REPAIR WELL (Other)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)
 - TD6576'. Ran 204 joints 4 1/2", 10.5#, KS production casing, 6564' set 5-21-74 at 6576'. Float collar set at 6562'. Stage tool set at 4675' and 2155'. Cemented first stage with 328 cu. ft. cement; second stage with 381 cu. ft. cement; third stage with 430 cu. ft. cement. WOC 18 hours. Top of cement at 1000'.
 - PBTD 6562'. Tested casing to 4000#-OK. Perf'd 6370', 6394', 6438', 6462', 6500', and 6528' with 1 shot per zone. Frac'd with 75,000# 6-24-74 40/60 sand and 89,250 gallons treated water. No balls dropped. Flushed with 4368 gallons water.



RECEIVED JUN 28 1974 U. S. GEOLOGICAL SURVEY FARMINGTON, N. M.

8. I hereby certify that the foregoing is true and correct SIGNED	TITLE	Drilling Clerk	DATE	June 27, 1974
(This space for Federal or State office use)				
APPROVED BY	TITLE		DATE	