orm 3160-5 November 1983) Formerly 9-331) DEPARTMENT OF THE INTERIOR verse side) BUREAU OF LAND MANAGEMENT		Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. 14-20-0603-8103			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)			Navajo Trib	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Tribe 7. UNIT AGREEMENT NAME	
Texaco Inc.		8. PARM OR LEASE HAME AR Trease (Lette			
3. ADDRESS OF OPERATOR D. O. BOY FF. Cortez. CO. 81321			9. WELL NO. 5	.]	
4. Location of Well (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface			Togita Dome	Penn "D"	
14. PERMIT NO. 16. ELEVATIONS (Show whether DF, RT, GR, etc.)			Sec. 27, T2		
16. Check Appropriate Box To Indicate Nature of Notice, Report, or C			San Juan r Other Data	New Mexico	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
FRACTURE TREAT	PCLL OR ALTER CASING HULTIPLE COMPLETE XX	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING C	ABING	
	CHANGE PLANS	(Other)	ults of multiple completion	on Well	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) Texaco Inc. Plans to plug the subject well as follows, subject to managerial approval. Managerial approval should require approximately 90 days. The					
approval. Manageri BLM office will be Navajo Tribe will b Objectives:	notified prior to	commencing plug	gging operation	ns. The	
1.) Spot 25 sxs cement plug in casing across all perfs. (6266-6238). 2.) Place 25 sxs cement in casing from 6050 to 5950 across Desert Creek. **3.) Place 25 sxs cement in casing from 4900 to 4800 to isolate organ Rock 5470' 5370'					
4.) Place 25 sxs cement in casing from 3700 to 3600 across DeChelly 2007-700 *5.) Place 25 sxs cement in casing from 1600 to 1550 to isolate Entrada 2009					
 6.) Place 25 sxs cement in casing from 800 to 700 across Dakota. 7.) Place 30 sxs cement in casing from 150 to surface. 8.) All other areas inside casing to be filled with 9.2 lb/gal Brine based mud. 					
9.) Abandonded hol 10.) Cement to be C	e marker to be en Class B need.	rected & location	n rehabilitate	d.	
NOTE: Cement	tops outside cas:	ing estimated at	surface.	. Now distribute de	
18. I hereby certify that the foregoing i		roa Suporintondo	n+ 7/	16/85	
SIGNED Chi-R. 277	TITLE A	rea Superintende	DATE	10/01	
(This space for Federal or State off APPROVED BY CONDITIONS OF APPROVAL, IF	TITLE	Exercise Section 1	JUL 2,4 1988		
BLM (5) - NMOGCC (3		ARM - Navajo Tri	time and a second		
*See Instructions on Reverse Side NMACC					