

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-0603-8103

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo Tribe "AR"

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Tocito Dome

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 27-T26N-R18W

12. COUNTY OR PARISH

San Juan

13. STATE

Ne w Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Texaco Inc.

Attention: T. Bliss

3. ADDRESS OF OPERATOR

P. O. Box 2100, Denver, Colorado 80201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

At surface

NE 1/4 Sec. 27

660' FWL & 1980' FWL, Sec. 27

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5656' Gr.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other)

Surf. & Prod. Casing

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

x

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well spudded 8:00 p.m. 5-25-74.

5-29-74: Ran 53 joints, 1,597', of 10-3/4" OD, 40.5#, casing set at 1595' KB. Cemented with 600 sacks Halliburton Lite, tailed in with 100 sacks Class "B" cement. Plug down 10:00 a.m. 5-28. Cement failed to circulate. Pumped 100 sacks regular cement with 3% CaCl down annulus.

Tested 10-3/4" casing and BOP blind and pipe rams with 500 psi for 30 minutes each. No loss in pressure.

6-16-74: Ran 190 joints, 6,383', of 7" OD, 20#, 23# & 24#, K-55, used LT&C casing, landed at 6370' KB. Cemented with 600 sacks Class "B" with 7# salt, 6# gilsonite, 1/2# barite, 3/4% CFR-2 per sack. Plug down 6:45 p.m. Cemented with 600 sacks Howco Lite, tailed in with 50 sacks Class "B" Heat through DV tool at 4281' KB. Plug down 8:45 p.m. 6-15.

18. I hereby certify that the foregoing is true and correct

SIGNED

T. Bliss

TITLE

District Superintendent

DATE

June 18, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

**USGS (3)
Farmington**

**OGCC (2)
Aztec**

TB ARM CGH The Navajo Tribe

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.