Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU ()F LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

Water Shut-Off

Conversion to Injection Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

14-20-0603-8103 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to/a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals Navajo Tribe 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Water Disposal Well 8. Well Name and No. 2. Name of Operator Navajo Tribe AR #8 Texaco Exploration & Production Inc. 9. API Well No. 3. Address and Telephone No. 30-045-21482 3300 N. Butler, Farmington N.M. 87401 (505)325-4397 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Tocito Dome, Penn D 11. County or Parish, State 660' FNL &1980' FWL Sec. 27 T26N / R18W San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction X Subsequent Report Non-Routine Fracturing Plugging Back

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Casing Repair

Texaco E & P Inc. has completed the following on the subject well:

Final Abandonment Notice

2-3-93 MIRU, NUBOP. Unset packer. TOH w/ 2-3/8" tbg. TIH w/ Bridge plug. Set RBP @ 6106', set packe @4432'. Test casing. Establish leak between 4314' & 4344'. TOH w/ BP and packer. Clean out sand and scal to TD. Rig up casing crew. Run in hole w/ float shoe, circulating packer, stage collar and 6118', 4-1/2" casing Cement casing liner to surface w/ 146 bbl cement, circ. 13 bbl to surface. Remove BOP. Set Casing head. Pressur test to 2000#. TIH w/ bit. Tag cement at 6022'. Drill out cement. TIH w/ packer, set at 6081'. Test to 1000# 2-17-93 met w/ Mr. Kenneth Lingo (CADMUS). Ran Mechanical Integrity Test at 700# for 30 min. No leak. Mr Lingo gave verbal approval to commence disposing. Return to disposal.



OIL CON. DIV.

	2151. 3
ED AUTHORITY  Title Area Manager	Date 3/2/93
	ACCEPTED FOR RECORD
	MAR 0.8 1993
	ED AUTHORITY

\*See Instruction on Reverse Side

or representations as to any matter within its jurisdiction