

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N00-C-14-20-5523

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo Tribal "Z"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Tocito Dome Penn. "D"

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SW/4 SW/4 Section 14,

T-26-N, R-18-W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

720' FSL & 570' FWL, Section 14, T-26-N, R-18-W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5635' CL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud & Set Casing ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The subject well was spudded at 6:00 PM November 3, 1974, and a 17-1/4" hole drilled to 143'. The 13-3/8" casing was set at 141' with 140 sacks Class "B" cement with 2% CaCl₂ on November 4, 1974. Waited on cement to set 14-1/2 hours and pressured casing to 800 psi for 1/2 hour OK. Reduced hole to 12-1/4" at 143' and continued drilling to 1534' where the 9-5/8" casing was set with 400 sacks Class "B" cement with 4% Gel and 2 pounds medium Tuf Plug per sack. Tailed in with 100 sacks Class "B" Heat on November 6, 1974. The cement circulated. Waited on cement to set 18 hours and pressured casing to 800 psi 1/2 hour OK. Reduced hole to 8-3/4" at 1534' and continued drilling.

NOV 25 1974

U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

W. L. Hamilton

TITLE

Area Adm. Supvr.

DATE

November 21, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.