

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. N00 C 19-20 5431	
2. NAME OF OPERATOR Texaco, Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Tribe "BS"	
3. ADDRESS OF OPERATOR P. O. Box 2100 Denver, Colorado 80201		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface SW¹/₄ NW¹/₄ Sec. 23 1980' FNL & 510' FNL, Sec. 23		8. FARM OR LEASE NAME Navajo Tribe "BS"	
14. PERMIT NO.		9. WELL NO. 4	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5677' GF		10. FIELD AND POOL, OR WILDCAT Tocito Dome	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23 T26N R18W	
		12. COUNTY OR PARISH San Juan	
		13. STATE New Mexico	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) <u>Surface casing</u> ☒	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12 22-74

Ran 2 joints of 13-3/8" OD. 48# H 40 ST&C casing, set at 82' KB. Cemented with 100 sacks regular w/3% CaCl. Plug down 6:00 a.m., 12-22 74. Cement circulated to surface.

12 25 74

Ran 29 joints (1980') of 9 5/8" OD. 36# K 55 ST&C casing, set at 1579' KB. Cemented with 600 sacks Howco Lite w/1% Flocele & 2% CaCl/sack, followed with 100 sacks regular w/2% CaCl. Plug down 3:45 p.m. 12 24 74.

Tested BOP equipment and casing with 800 psi for 30 minutes; no loss in pressure.

18. I hereby certify that the foregoing is true and correct

SIGNED Tommy Bliss TITLE District Superintendent DATE Dec. 24, 1974

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

USGS(3) OGCC(2) TB ARM CGH The Navajo Tribe
Farm. Aztec

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.