

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY
3. ADDRESS OF OPERATOR
501 Airport Drive Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1850' FNL x 2010' FWL, Section 22,
AT SURFACE: T-26-N, R-18-W
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☒
(other)

5. LEASE
14-20-603-5034
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Navajo Tribe
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Navajo Tribal "U"
9. WELL NO.
18
10. FIELD OR WILDCAT NAME
Tocito Dome - Penn "D"
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
SE/4 NW/4 Section 22,
T-26-N, R-18-W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
30-045-21711
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5650' GL 5663' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
Abandonment operations commenced on 12/15/78. Tripped in hole with tubing and cement retainer set at 3162'. Pumped 160 sx Class "B" Neat below retainer. Sting out of retainer. Spotted 60 sx Class "B" Neat on top of retainer. Perforated 7" casing with 4 shots at 1550'. Tripped in with tubing and cement retainer. Set at 1488'. Squeezed perfs with 150 sx Class "B". Spotted 40 sx Class "B" Neat on top of retainer. Dug out and cut off wellhead. Spotted 30 sx plug Class "B" Neat at surface. Erected P&A marker and service unit released on 12/19/78.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE _____ Adm. Supvr. DATE _____ 12/22/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

DISTRICT ENGINEER

Nymoc