## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Dac. 1973	Budget Bureau No. 42-R1424		
UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	SF 079052		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME		
reservoir, Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas sother	Rincon Unit		
well well well other	9. WELL NO.		
2. NAME OF OPERATOR	97A		
EL PASO NATURAL GAS CO.	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Blanco Mesa Verde		
BOX 990, FARMINGTON, NEW MEXICO	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 18, T-27-N, R-6-W		
AT SURFACE: 910'S, 1110'E	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL:	Rio Arriba New Mexico		
AT TOTAL DEPTH:	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
	6606 GL		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			
FRACTURE TREAT			
REPAIR WELL	(NOTE: Report results of multiple completion or zone		

EL PASO NATURAL GAS CO. 3. ADDRESS OF OPERATOR BOX 990, FARMINGTON, NEW MEXICO 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1 below.) AT SURFACE: 910'S, 1110'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC REPORT, OR OTHER DATA SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF  $\square$ FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON\* (other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/5/78: Spudded well. Drilled surface hole. Ran 5 joints 9 5/8", 32.3# H-40 surface casing, 214' set at 227'. Cemented with 224 cu. ft. cement. Circulated to surface. WOC 12 hours; held 600°/30 minutes.



		Set @	Ft.
and correct			
TITLE Drilling Clerk	DATE	9/11/78	
his space for Federal or State office us	e;		
TITLE	DATE		
	and correct	and correct	

\*See Instructions on Reverse Side