

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Tr. 109(NCO-C-14-20-4157)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo 1-5

9. WELL NO.

1-5

10. FIELD AND POOL, OR WILDCAT

Wildcat-Beau. Mtn. Area

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 5-T26N-R19W

14. PERMIT NO.

15. ELEVATIONS (Show whether LF, RT, GR, etc.)

5937 Grd; 5948 KB

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Status Report-1

PULL OR ALTER CASING

☐  
☐  
☐  
☐

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

☒

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐  
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Status Report No. 1

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

☐  
☐  
☐  
☒

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud April 27, 1975 - TD 6087 feet 5/20/1975

17 1/4" hole - 13 3/8" 48# csg - 64 feet cemented 130 sx Class "B" plus 2% CaCl

12 1/4" hole - 8 5/8" 24# csg - 1421 feet cemented w/725 sx Class "B" plus 2% CaCl

7 7/8" hole - 4 1/2" 10 1/2# csg - 6076 feet cemented w/380 sx 50-50 pozmix plus 2% gel

DST No. 1 (Straddle Packer Test - "Barker Creek" Zone) Present depth 5884'

Interval 5640-5719 Open 30 min, fair blow, slid approx 16', had to put on another joint &amp; close tool, opened tool with good blow, slid an additional 5 feet to

bottom. Had a good blow throughout, shut-in 60 min. opened 60 min. GTS in 90 min

(Flammable) TSTM-Shut-in 90 min. Rec. 1050' GCM, 950' GCSW. Bottom packers not

holding. IHP-2761 psig, FHP-2743 psig IFP (1) 613 psig FFP (1) 706 psig

IFP (2) 777 psig, FFP (2) 914 psig ISIP (1) 2722 psig, FSIP (2) 2716 psig

Temp. 140°F

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert E. Lauth

TITLE

Agent-Geological Consultant

DATE

6-5-75

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED

JUN 9 1975

U. S. GEOLOGICAL SURVEY