-UJGS L-Mellug	h Adale					/		
Form: 9-331 (May 1963)						5. LEASE DESIGNATION AND SERIAL NO.		
	GEOLOGI	CAL SURVEY			M 12028 Indian, allottei	E OR TRIBE NAME		
SUN (Do not use this	DRY NOTICES AT form for proposals to drill Use "APPLICATION FOR	OF REPORTS OF TO GEORGE PERMIT—" for such p	ON WELLS back to a different reserve roposals.)		10 day 10 day 10 day 10 day 10 day 10 day			
OIL GAS WELL WELL	X OTHER	**************************************			NIT AGREEMENT NA			
2. NAME OF OPERATOR				8. F	ARM OR LEASE NAM	ME NOTE OF THE PERSON OF THE P		
Jerome P.	McHugh				haco Plan	t		
3. ADDRESS OF OPERATOR		07001		9. w	ELL NO. 128	Constant Con		
BOX 234,	Farmington, NM Report location clearly and i	87401 n accordance with any	State requirements.	10. 1	FIELD AND POOL, O	<u> </u>		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 850 * FNL - 1510 * FEL					Indesignat			
					SEC., T., R., M., OR I SURVEY OR AREA	BLK. AND		
				9	Sec 20, T2	6N, R12W		
14. PERMIT NO.	15. ELEVA	TIONS (Show whether D			COUNTY OR PARISE	13. STATE		
		60371	GR	<u> </u>	San Juan	L E NM E		
16.	Check Appropriate	Box To Indicate 1	Nature of Notice, Rep	ort, or Other	Data 🖁 🖁 🗒	图 第2名可		
	NOTICE OF INTENTION TO:			SUBSEQUENT R	EPORT OF			
TEST WATER SHUT-0	FF PULL OR ALT	TER CASING	WATER SHUT-OFF		REPAIRING	WELL		
FRACTURE TREAT	MULTIPLE CO	OMPLETE	FRACTURE TREATM	ENT	AUTERING C			
SHOOT OR ACIDIZE	ABANDON*		SHOOTING OR ACID	· \				
REPAIR WELL	CHANGE PLA	NS	(Other)	ort results of mt	Squeez ltiple-completion			
•				SCOURT TO SHOW SERVED BY A	of sbandonness (benedation) and bottom) and bottom) and benedation of the control	Hod ninder capolited of disease to the first the second of the first the second of the first the second of the first		
		SEE ATTACH	ED REPORT		de egreça d' eneza (14 de m eneza (15 de m eneza de mara eneza de mara eneza de mara eneza de mara eneza de mara eneza de mara de mara eneza de mara de mara eneza de mara de	design of the control		
			No.	L JUN	Star of the control o	in i		
		F	11 1976 JUN 2 1976	fr o Carre	the specific instructions. The control positive of the substantial substantia	e to designate to be all entre to be all entre to be all entre to the control of the total entre to the total entre total entre to the total entre tot		
18. I hereby certify the	the foresoing is true and		IL CON. COM		Solida So			
SIGNED .	A. Nugan	TITLE	Engineer		рать 6-	25-76		
(This space for Fed	eral or State office use)							
APPROVED BY	V	TITLE			DATE	<u>= :: </u>		
CONDITIONS OF A	PPROVAL, IF ANY:					\$ 		

SUBSEQUENT REPORT OF SQUEEZE

4-10-76

BJ squeezed perfs 1136-1140' down 2-7/8" csg w/35 sx Class "B" with .2% Aquatrol (fluid loss additive). Established rate of 4 BPM @ 750 psi before pumping cement. Calculated displacement to leave 50' cement in csg. Max and final press 100 psi. Job complete 3:45 PM 4-10-76.

4-14-76

BJ re-squeezed perfs 1136-1140' down 2-7/8" csg w/35 sx Class "B" with .2% Aquatrol (fluid loss additive). Established rate of 2-1/2 BPM @ 1200 psi before squeezing. Max squeeze press 2200 psi. Job complete 6:50 PM 4-14-76.

4-16-76

Moved in and rigged up Wilson Drilling Company rig. Ran 1-1/4" tbg in hole. Tagged cement @ 1100'. Drilled 40' cement. Circulated out frac sand to 1268' (baffle and plug). Pulled 1-1/4" tbg out of hole and released rig. Rigged up Farmington Well Service pulling unit. Attempted to run bond log by GO International, unable to get below 1121' with 2-3/8" tool. Swabbed csg to 800'. Perforated by GO International one shot/ft 1136-1140' and 1125-1129'. Swabbed well down. No indication of gas or fluid entry.

5-19-76

Western Company frac Pictured Cliffs formation 1125-1140' using 652 hp, 15,000 lbs 10-20 sd, 476 bbls wtr, 2-1/2# FR-2/1000 gal wtr. Spearheaded frac w/100 gal 15% HCl, Breakdown 1700 psi, Max 1600 psi, Avg 1400 psi, Min 1300 psi, Final 1650 psi, ISDP 1050 psi, 10-Min SI 200 psi, Avg IR 19 BPM. Made 3 ball drops of 5 balls each, had increase on last 2 drops. Shut well in.

6-2-76

Moved in and rigged up Farmington Well Service swabbing unit. Ran 35 jts 1-1/4" OD 2.4# J-55 tbg. TE 1137.48' set @ 1135' GR. Swabbed tbg. Fluid level staying approx 300'. Csg press 175# psi. Well won't flow. Shut well in. Rigged down swabbing unit.

