

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 12028

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chaco Plant

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Undesignated - PC

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 21, T26N, R12W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

Box 234, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1500' FNL - 960' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6030' GR

## 18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-1-75

Moved in Morrow Drilling Company rig and spudded 7-7/8" hole @ 2:30 PM 10-31-75. Drilled w/air to 36' and ran 2 jts 5-1/2" OD 14# used csg, TE 35.80' set @ 36' GR. Cemented w/5 sx cement. Job complete 3:30 PM 10-31-75. WOC.

11-6-75

TD 1244', finished drilling 4-3/4" hole to 1244'. Ran Go International electric log (logger's TD 1240'). Ran 41 jts 2-7/8" OD 6.4# 10R NEUE tbq for csg, TE 1231.42' set @ 1230' GR. Cemented w/100 sx 2% lodense w/1/2# cello-flake/sk, good mud returns while cementing (cement circulated approx 2 bbls), reciprocated pipe while cementing. POB 5:45 PM 11-5-75.



NOV 12 1975

U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct.

SIGNED

  
Thomas A. Dugan

TITLE

Engineer

DATE

11-10-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side