

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 13752

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chaco Plant

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Chaco Plant - PC

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 5, T26N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

1. OIL ☐ GAS ☒
WELL WELL OTHER

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

Box 234, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1800' FNL - 990' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5938' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:


WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

3-29-76

Moved in and rigged up Morrow Drilling Company rig. Drilled rat hole and spudded 8-3/4" hole @ 10:00 AM 3-28-76. Drilled to 45' and ran one jt 7" OD 20# 8R ST&C csg, TE 43.50' set @ 49' RKB, cemented to surface w/8 sx. Job complete @ 2:00 PM 3-28-76.

4-4-76

TD 1345'. Ran 42 jts 2-7/8" OD 6.5# 8R EUE tbg for csg, TE 1335.27' set @ 1344' GR, cemented by BJ w/90 sx 2% lodense w/1/4# cello-flake/sk. Good mud returns while cementing. Reciprocated pipe while cementing. Max cementing press 1000 psi. POB 1:10 PM 4-3-76.



RECEIVED
APR 7 1976
U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

Thomas A. Dugan

TITLE

Engineer

DATE

4-5-76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side