

5 BLM

1 McHugh

1 Tenneco

1 File

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ P & A

2. NAME OF OPERATOR
Jerome P. McHugh

3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 850' FSL - 1560' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U.S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged and abandoned as follows:

1. Pulled 16 jts. 1 1/2" O.D., 2.4#, V-55, 10 Rd, EUE tubing and Baker Model "C" invertible packer.
2. Filled 2-7/8" O.D., 6.5#, 8 Rd, EUE tubing for casing from PBTD: 1284' to surface, using 35 sx of class "B" cement 5-20-83.
3. Installed permanent dry hole marker and cut off tie-downs.
4. Filled all pits.
5. Cleaned and restored location per BLM instructions.

Ready for inspection.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Sherman E. Dugan TITLE Agent

DATE 7-1-83

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AS AMENDED

DEC 1-8 1984

/s/ J. Stan McKee
M. MILLENBACH
AREA MANAGER

Approved as to plugging of the well bore. NMOCC
Liability under bond is retained until
surface restoration is completed.

Instructions on Reverse Side