

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other Instructions on re-
verse side)Form approved.
Budget Bureau No. 42-01424

5. LEASE DESIGNATION AND SERIAL NO.

NM 26354

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

Box 234, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1500' FNL - 900' FEL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chaco Plant

9. WELL NO.

20

10. FIELD AND POOL, OR WILDCAT

Went Nipp-PC Extension

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 27 T26N R12W

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, FE, GR, etc.)

6153' GR

12. COUNTY OR PARISH

San Juan

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

CSG

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-27-79

Ran 43 jts 2-7/8" OD 6.4# CW-55 10R NEUE tbq for csg. TE 1295.78' set @ 1295' GR. Had good mud returns and reciprocated pipe while cementing. Preflushed hole w/100 gals CW-7 chemical wash. Cemented w/75 sx 65-35 poz w/12% gel w/1/4# flo cele per sx followed by 50 sx neat w/1/4# flo cele per sx. Had good cement to surface. Bumped plug w/1500 psi. Released to 750 psi. Shut in. POB 3:00 p.m. 2-26-79.

18. I hereby certify that the foregoing is true and correct

SIGNED

Thomas A. Dugan

TITLE

Agent

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR 1 - 1979

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

DATE

2-27-79

DATE

*See Instructions on Reverse Side

Nmoce