

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION OR SURVEY NO.
N00-C-14-20-343T

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

OPERATOR **TEXACO INC.** Attention: **G. L. Eaton**

2. ADDRESS OF OPERATOR **P. O. Box 2100, Denver, Colorado 80201**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.) **SW $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 23**
At surface **1980' FNL & 810' FWL, Sec. 23**

14. PERMIT NO.

15. ELEVATION (Give whether DF, RT, GR, etc.) **5671' GR**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. NAME OF LEASE **Navajo Tribe "BS"**

9. WELL NO. **4 R**

10. FIELD OR BOOTH OR WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR REBT. NO. **Sec: 23 T26N-R13W**

12. **San Juan** **New Mexico**

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well on 2-17-77.

Ran 2 joints (97') of 13-3/8" OD 48# H-40 ST&C new casing. Set at 87' and cemented with 125 sacks Class "B" with 2% CaCl₂. Plug down at 6:00 AM, 2-18-77. Cement circulated to surface.

Ran 40 joints (1644') of 8-5/8" OD X-52 28.55# ST&C new casing. Set at 1640' KB and cemented with 600 sacks Class "B" Lite cement with 1/4# Flo-seal per sack and 100 sacks regular cement with 2% CaCl₂. Plug down at 7:15 PM, 2-21-77 with 1200 psi. Cement circulated.

Tested blowout preventer equipment and casing at 700 psi for 30 minutes. No loss in pressure.

18. I hereby certify that the foregoing is true and correct

District Superintendent

Feb. 24, 1977

SIGNED **SIGNED: G. L. EATON**

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

USGS(1) 0000(2) ANY: GLE
Farmington Aztec

ARM JHP The Navajo Tribe

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.