

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR
DOME PETROLEUM CORPORATION3. ADDRESS OF OPERATOR 501 Airport Drive,
Suite 107, Farmington, New Mexico 874014. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1190' FNL, 1090' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) PLUG BACK AND CHANGE ZONES		

5. LEASE
NM 0560222

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
FUSSELMAN FEDERAL

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

WAW FRUITLAND - PICTURED CLIFF

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 17, T26N, R12W

12. COUNTY OR PARISH

SAN JUAN

13. STATE

NEWMEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5931 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Dome Petroleum Corp. proposes to squeeze and set cement plug 200' above Pictured Cliff perforations at 1086' to 1105'. Cement used will be 15 sacks class "B" cement with 2% CaCl. Top of plug will be at 886'. A wiper plug will be used when displacing cement. A Farmington sand completion will then be attempted. Estimated starting date 07/25/79.

Verbal approval received from Mr. James F. Sims at 3:30 PM, 07/19/79.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H.D. Hollingsworth TITLE DRILLING FOREMAN DATE July 19, 1979

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL IF ANY

TITLE _____ DATE _____

NMOCC

*See Instructions on Reverse Side

