UNITED STATES PARTMENT OF THE INTERIOR

	5. LEASE		
	NM 0560223		
I	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
	7. UNIT AGREEMENT NAME		
ent			
	8. FARM OR LEASE NAME		
	Frew Federal		
	9. WELL NO.		
	8		
	10. FIELD OR WILDCAT NAME Fruit		
	NIPP Pictured Cliff		
,	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
17	AREA		
	Sec 19, T26N, R12W		
	12. COUNTY OR PARISH 13. STATE		
	San Juan NM		
	14. API NO.		
ĊE,			
	15. ELEVATIONS (SHOW DF, KDB, AND WD)		

DEDADIMENT OF THE INTLINOR	111. 0500110
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
eservoir, use rollii 3-331-0 to	Frew Federal
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR	8
Dome Petroleum Corp.	10. FIELD OR WILDCAT NAME ANIEL Fruit
3. ADDRESS OF OPERATOR 501 Airport Drive, Suite 107, Farmington, NM	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17	Sec 19, T26N, R12W
below.) AT SURFACE: 1850' FSL & 1450" FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan NM
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	TO THE TIME (CHOW DE KDP AND WD)
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6057 GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
ABANDON*	
(other) Spud & set surface	•

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-8-79 - Spuded 7 7/8" hole at 12:00 noon 1-8-79. Fan 1 joint (39') $5\frac{1}{2}$ " O.D., 15.50#, K55, ST&C Casing. Set at 43' KB. Cemented with 35 sacks class "B" cement with 3% CaCl. Plud down at 2:05 PM 1-8-79. Circulated cement.

	Set @Ft.
Subsurface Safety Valve: Manu. and Type	Set W
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling F	oremandate 1-19-79
H. D. Hallingswarth (This space for Federal or State of	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE