

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well    gas ☒ well    other ☐

2. NAME OF OPERATOR  
Dome Petroleum Corp.

3. ADDRESS OF OPERATOR  
501 Airport Dr., Suite 107, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1687' FSL & 1850' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) <u>Proposed Procedure Changes</u>		

5. LEASE  
NM 0560223

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Frew Federal

9. WELL NO.  
14

10. FIELD OR WILDCAT NAME  
Nipp Pictured Cliff

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 29, T26N, R12W

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6066' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Hole Size	Casing Size	Weight	Setting Depth	Quantity Cement
8 3/4" or	5 1/2" or	15.5# or	40'	35 sacks
9 7/8"	7"	20#		
4 3/4"	2 7/8"	6.5#	1300'	150 sacks

Spud 8 3/4" or 9 7/8" hole with native mud. Drill 45' run and cement 5 1/2" or 7" casing as above.  
Drill 4 3/4" hole from under surface casing. If productive run 2 7/8" casing and cement as above.

RECEIVED  
DEC 12 1978  
GEOLOGICAL SURVEY

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Hoffingworth TITLE Drilling foreman DATE December 11, 1978

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

Nmoce

