AT TOTAL DEPTH:

ABANDON*

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

		Budget Bur		2-R1424
	5. LEASE	:	-	ė
Ì	NM 0560 2 23		<u> </u>	
	6. IF INDIAN, ALLOT	TEE OR T	RIBE NA	ME
-			<u> </u>	·
	7. UNIT AGREEMEN	IT NAME	A 1.	· · . <u>.</u>
t		<u> </u>	<u> </u>	
_	8. FARM OR LEASE			:
	Frew Federa			-1
_	9. WELL NO.	•		· -
	13	·		i.
_	10. FIELD OR WILDO			
	Nipp Picture			
	11. SEC., T., R., M., (OR BLK.	AND SUR	VEY OR
,	AREA Sec 29, T26N	, R12W	1	
	12. COUNTY OR PAR			ico
	San Juan	I NE	w Mex	iço
	14. API NO.		3.4	Ţ
•		2 - 5	<u> </u>	
	15. ELEVATIONS (SE	IOW DF.	KDB. AL	יםש מוי

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME				
reservoir, Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Frew Federal				
well gas other 2. NAME OF OPERATOR	9. WELL NO.				
Dome Petroleum Corp. 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Nipp Pictured Cliff				
501 Airport Drive, 107, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)	11. SEC., T., R., M., OR BLK. AND SURVEY C AREA Sec 29, T26N, R12W				
AT SURFACE: 1190'FSL & 1850' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico				

16. CHECK APPROPRIATE BOX	TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	•	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	·	6065GR
REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF		
FRACTURE TREAT		
SHOOT OR ACIDIZE		
REPAIR WELL		(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING		change on Form 9-330.)
MULTIPLE COMPLETE		
CHANGE ZONES		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Hole Size	Casing Size	Weight	Setting Depth	Quantity Cement
8 3/4" or	5 1/2" or	15.5# or	40'	35 sacks
9 7/8"	7"	20#		
4 3/4"	2 7/8"	6.5#	1300'	150 Sacks

Spud 8 3/4" or 9 7/8" hole with native mud. Drill 45, or 7" casing as above. Run and cement 5 1/2" If productive, run 2 7/8" casing Drill 4 3/4" hole from under surface casing. and cement as above.

		ç; ;		ระบาร์สกา	101 991 81 -10 337 - 8 34 915	
Subsurface Safety Valve: Manu. and Type			Set	@		Ft.
18. I hereby certify that the foregoing is true and correct				र्िं±		
SIGNED WILL Drilling Foreman DATE		December 11, 1978				
	01.1. (()					

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

(other) Proposed procedure changes

See Instructions on Reverse Side

NMUCE

