UNITED STATES

	Budget Bureau No. 42-R1424
	5. LEASE NM 0560223
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	7. UNIT AGREEMENT NAME
nt	8. FARM OR LEASE NAME Frew Federal
	9. WELL NO.
	10. FIELD OR WILDCAT NAME Nipp Pictured Cliff
17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 30, T26N, R12W
	12. COUNTY OR PARISH 13. STATE San Juan New Mexico
Œ.	14. API NO.
,,	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	UTED MIX
	(NOTE: Report results of multiple completion or zon change on Form 9-330.)

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a difference or such proposals.) 1. oil well \Box other 2. NAME OF OPERATOR Dome Petroleum Corp. 3. ADDRESS OF OPERATOR 501 Airport Dr., Suite 107, Farmington, NM 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space below.) 790' FSL & 790' FWL AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTI REPORT, OR OTHER DATA SUBSEQUENT REPORT OF REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON.* (other) Proposed procedure changes

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Hole Size 8 3/4" or 5 1/2" or 15.5# or 40' 35 sacks 9 7/8" 7" 20# 4 3/4" 2 7/8" 6.5# 1300' 150 sacks Spud 8 3/4" or 9 7/8" hole with native mud. Drill 45' run and cement 5 1/2" or 7" casing as above. Drill 4 3/4" hole from under surface casing. If a reductive, un 2 7/8" casing and cement as above. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED All Hollingsworth TITLE Drilling Foreman DATE DECEmber 11, 1978 APPROVED BY TITLE DATE DATE				-ttime Donth	Quantity Cement			
8 3/4" or 5 1/2" or 15.5# or 40' 9 7/8" 7" 20# 4 3/4" 2 7/8" 6.5# 1300' 150 sacks Spud 8 3/4" or 9 7/8" hole with native mud. Drill 45: run and cement 5 1/2" or 7" casing as above. Drill 4 3/4" hole from under surface casing. If productive, run 2 7/8" casing and cement as above. Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type TITLE Drilling Foreman DATE December 11, 1978 TITLE Drilling Foreman DATE TITLE Drilling Foreman DATE December 11, 1978	Hole Size	Casing Size	<u>Weight</u>	setting behan				
Spud 8 3/4" or 9 7/8" hole with native mud. Drill 45; run and cement 5 1/2" or 7" casing as above. Drill 4 3/4" hole from under surface casing. If an oductive, run 2 7/8" casing and cement as above. Subsurface Safety Valve: Manu. and Type			15.5# or	40'	35 sacks			
Spud 8 3/4" or 9 7/8" hole with native mud. Drill 45 run and cement 5 1/2" or 7" casing as above. Drill 4 3/4" hole from under surface casing. If an aductive, run 2 7/8" casing and cement as above. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use)		711		:				
Spud 8 3/4" or 9 7/8" hole with native mud. Drill 45; run and cement 5 1/2" or 7" casing as above. Drill 4 3/4" hole from under surface casing. If productive, run 2 7/8" casing and cement as above. Subsurface Safety Valve: Manu. and Type Set @Ft. 18. I hereby certify that the foregoing is true and correct SIGNED ALL LANGE TITLE Drilling Foreman DATE December 11, 1978 TITLEDATE		7 2 7/8"		1300'	150 sacks			
7" casing as above. Drill 4 3/4" hole from under surface casing. If areductive, run 2 7/8" casing and cement as above. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use) TITLE DAME		·		٠٠٠ پ سر				
7" casing as above. Drill 4 3/4" hole from under surface casing. If an aductive, run 2 7/8" casing and cement as above. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use) TITLE DAME	or 10 2/4% on 0.7/8% hole with native mud. Drill 45 Fun and cement 5 1/2% or							
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use) APPROVED BY	Spud 8 3/4" or 9 //o note with haction many							
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use)	7" casing as above.							
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use) APPROVED BY	Drill 4 3/4" note from under surrade							
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use)	cement as above.		I was	8 1910 = 1				
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use) APPROVED BY			250	L'EY T				
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use)	·		\cdot $\rho_{\mu_{\sigma_{\sigma}}}$	State West	9			
18. I hereby certify that the foregoing is true and correct SIGNED TITLE Drilling Foreman DATE December 11, 1978 (This space for Federal or State office use) APPROVED BY	Subsurface Safety Valve: Manu. and Type Set @ Ft.							
SIGNED TITLE Drilling Foreman DATE DECEMBER 11, 1979 (This space for Federal or State office use) APPROVED BY TITLE Drilling Foreman DATE DATE			No. 1					
APPROVED BY TITLE DATE	18. I hereby certify that the foregoing is true and correct							
APPROVED BY TITLE DATE	Sur Illabilia	round TITLE Dr	illing Foreman	_ DATEDECEMBET TO				
APPROVED BY TITLE DATE	H. D. Ho Mingsworth							
APPROVED BY	(TIMS SPACE TO THE							
TOUR OF APPROVAL IF ANY:	ADDROVED BY			DATE	OF OF STANK			
CONDITIONS OF ACTION AND ADDRESS OF ACTION A	CONDITIONS OF APPROVAL	IF ANY:		1	011			

*See Instructions on Reverse Side

NMOCE