UNITED STATES DEPARTMENT OF THE INTERIOR

| | DOGGE DUTON 11042-11424 |
|---|--|
| | 5. LEASE |
| | NM 0560223 |
| | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| - | |
| | 7. UNIT AGREEMENT NAME |
| t | ** |
| | 8. FARM OR LEASE NAME |
| | Frew Federal |
| | 9. WELL NO. |
| | 7 |
| | 10. FIELD OR WILDCAT NAME |
| | Nipp Pictured Cliff |
| | 11. SEC., T., R., M., OR BLK. AND SURVEY O |
| 7 | AREA |
| | Sec 19, T26N, R12W |
| | 12. COUNTY OR PARISH 13. STATE |

| | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | | |
|---|---|--|--|
| GEOLOGICAL SURVEY | | | |
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different | 7. UNIT AGREEMENT NAME | | |
| reservoir. Use Form 9–331–C for such proposals.) | 8. FARM OR LEASE NAME | | |
| 1. oil gas other | Frew Federal | | |
| Well Well | 9. WELL NO. | | |
| 2. NAME OF OPERATOR Dome Petroleum Corp. | 10. FIELD OR WILDCAT NAME | | |
| 3. ADDRESS OF OPERATOR | Nipp Pictured Cliff | | |
| 501 Airport Dr., Suite 107, Farmington, NM | 11. SEC., T., R., M., OR BLK. AND SURVEY OF | | |
| 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) | AREA Sec 19, T26N, R12W | | |
| AT SURFACE: 1190' FSL & 790' FWL | 12. COUNTY OR PARISH 13. STATE | | |
| AT TOP PROD. INTERVAL: | San Juan New Mexico | | |
| AT TOTAL DEPTH: | 14 . API NO. | | |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, | | | |
| REPORT, OR OTHER DATA | 15. ELEVATIONS (SHOW DF, KDB, AND WD 6130 GR | | |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: | | | |
| TEST WATER SHUT-OFF | | | |
| SHOOT OR ACIDIZE | : | | |
| REPAIR WELL | (NOTE: Report results of multiple completion or zon | | |
| PULL OR ALTER CASING | change on Form 9-330.) | | |
| MULTIPLE COMPLETE | | | |
| ABANDON* | • | | |
| (other) Proposed procedure changes | | | |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state | e all pertinent details, and give pertinent dates | | |

including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

| 8 3/4" or | | <u>Weight</u> 15.5# or | Setting Depth 40' | Quantity Cement 35 sacks | | | | |
|--|-------------------------------|---------------------------|----------------------|--|--|--|--|--|
| 9 7/8" 4 3/4" | 7 " 2 7/8" | 20# 6.5# | 1300' | 150 sacks | | | | |
| 5 1/2" or 7" | casing as above. | | Drill to 45', ru | E STATE OF S | | | | |
| and cement a | note from under s s above. | Y 1 3 4 | Treductive | run 2 //8" casing | | | | |
| Subsurface Safety Valve: Manu. and Type DEC 1 2 1978 Set @ Ft. 18. I hereby certify that the foregoing is true and correct Dec 1 2 1978 Prilling Exercises Proceeding 11 1079 | | | | | | | | |
| H. D. Hollingsworth | | | | | | | | |
| (This space for Federal or State office use) | | | | | | | | |
| APPROVED BYCONDITIONS OF APPRO | DVAL, IF ANY: | TITLE | PATE | 4 1978 | | | | |
| las | • | See Instructions on Rev | verse Side OIL COR | T. 3 | | | | |

NMOCE