

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒  
well well other

2. NAME OF OPERATOR  
Dome Petroleum Corp.

3. ADDRESS OF OPERATOR 501 Airport Dr.  
Suite 107, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1190' FSL & 790' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Run production casing	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to 1350'. Ran 43 joints (1329') 2 7/8", 6.5#, J55 casing. Casing landed at 1333' KB. Cemented with 175 sacks Class "B" cement with 3% CaCl. Plug down at 5:30 PM 2/4/79.

5. LEASE  
NM 0560223

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Frew Federal

9. WELL NO.  
7

10. FIELD OR WILDCAT NAME  
NIPP Pictured Cliff

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 19, T26N, R12W

12. COUNTY OR PARISH 13. STATE  
San Juan NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6130 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Hollingsworth

TITLE Drilling Foreman

DATE 2-6-79

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL IF ANY:

TITLE

DATE

NMOCC

