

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Sanan, Ltd.
3. ADDRESS OF OPERATOR
P.O. Box 255, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1450' fsl 1190' fel
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☒
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF-030008
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A
7. UNIT AGREEMENT NAME
N/A
8. FARM OR LEASE NAME
Crab
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
WAW Fruitland - P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
S8-T26N-R12W, N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
New Mex.
14. API NO.
30-045-23246
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5996 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose moving on pulling unit, installing mastervalue, pressure testing 2 7/8" casing, swabbing hole to 1000', rig stripper head and perforate casing with 1 SPF from 1180-1188'. Acidize perfs with 250 gal. mud acid. If productive will run 1 1/2" tbg. with packer above perfs and complete natural. If not productive, will plug & abandon by filling existing 2 7/8" surface with Class B cement, & erect dry-hole marker & clean, level & seed location in accordance with Federal regulations to commence approximately August 15, 1979.

RECEIVED
AUG 9 1979
U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm R. Speer TITLE Agent DATE August 9, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED
AUG 23 1979
John W. Wierke
DISTRICT ENGINEER