

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other Dry
2. NAME OF OPERATOR
Sanan, Ltd.
3. ADDRESS OF OPERATOR
P.O. Box 255, Farmington, MI 48401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1450' fsl, 1190' fel
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input checked="" type="checkbox"/>

(other) _____

5. LEASE
SE-000000
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A
7. UNIT AGREEMENT NAME
N/A
8. FARM OR LEASE NAME
Crab
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
WAW Fruitland - P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SE-76H-R12H, N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
30-045-23246
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5996 Gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Nov. 15, 1979 - Tested Well, no gas, no shut-in pressure.

Nov. 16, 1979 - Rigged up cementing truck, pumped 7½ bbls. neat cement slurry in to 2 7/8" tubing. Pressure build-up to 350 psi while pumping. Filled tubing to surface. Erected 4½" dry-hole marker over 2 7/8" stub and cemented. Filled pits and leveled location.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED William D. Sims TITLE Agent DATE November 16, 1979APPROVED BY James F. Sims TITLE _____ DATE _____
CONDITIONS OF APPROVAL _____**APPROVED**FOR JAMES F. SIMS
DISTRICT ENGINEER

*See Instructions on Reverse Side

