

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Sanan, Ltd.
3. ADDRESS OF OPERATOR
P.O. Box 255, Farmington, N.H. 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1450' fsl 1190' fel
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
(other) drilling to TD

5. LEASE
SF-030008
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
None
7. UNIT AGREEMENT NAME
None
8. FARM OR LEASE NAME
Crab
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
WAW-Fruitland - P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
S8-T26N-R12W, N.M.P.M.
12. COUNTY OR PARISH 13. STATE
San Juan New Mexico
14. API NO.
30-045-23246
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5996 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

July 30, 1979 - Drilled 4 3/4" hole to total depth of 1270 ft. Ran Electrical Survey, Gamma-ray & density log to TD of 1266 ft. Ran 41 jts (1271.68') of 2 7/8", 6.5#, N-80, 8-rnd EUE casing to TD of 1270 ft. Preceded cement with 5 BW and 10bbls C-100 chemical wash. Cemented with 150 sacks 50/50 Class B-Poz mix slurry with 1/2 lb./sack D-29 cellophane, 2% gel and 2% CaCl. Followed by 5.3 bbls. Class B neat slurry. Pumped down latching plug @ 1100-1300 psi. & maintained 1500 psi while waiting on cement 24 hrs. Will attempt completion later.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____

Rt. _____

18. I hereby certify that the foregoing is true and correct

SIGNED _____

TITLE Agent

DATE August 2, 1979

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: _____

mymock