5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	NM 7787
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
eservoir. Use Form 9–331–C for such proposais.)	8. FARM OR LEASE NAME
1. oil gas X other	DOME FEDERAL 25-26-13 9. WELL NO.
2. NAME OF OPERATOR	1
DOME PETROLEUM CORPORATION	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 501 Airport Drive	WAW FRUITLAND - PICTURED CLIFF
Suite 107, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	AREA SEC 25, T26N, R13W
AT SURFACE: 1450' FNL, 1190' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	1
AT TOTAL DEPTH:	SAN JUAN NEW MEXICO 14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	TAL ALLINO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	6119 GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0113 01
TEST WATER SHUT-OFF TRACTURE TREAT	
FRACTURE TREAT SHOOT OR ACIDIZE T	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING 🗍	change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
other) PLUG BACK AND CHANGE ZONES	
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinen 	rectionally drilled trive subsurface leastions and
Dome Petroloum Corp. property	
Dome Petroleum Corp. proposes to squeeze Pict 1191', 1194'-1198', 1210'-1212', 1218'-1222'	ured Cliff perforations at 1189'-
Cement used will be 15 sacks class "B" cement	and set top; of plug at 989'
be used when displacing cement.	with 2% CaCl. A wiper plug will
A Farmington sand completion will then be att $08/01/79$.	empted. Estimated starting date
Verbal approval received from Mr. James F. Si	ms at 3:30 PM = 07/19/79
	in the second of
	្រីត្រីឡូក៏ប្រកិប្បតិ៍
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED H.D. HOLLEGGSWORTH TITLEDRILLING FOREM	AN DATE July 19, 1979
(This space for Federal or State offi	ce use)
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVA. F ANY	APPROVED
nymocc	
•	JUL 2 3 1979 F

*See Instructions on Reverse Side

ACTING DISTRIC', ENGINEER