

THIS IS AN INTENT TO ABANDON  
AS WELL AS AN ACIDIZE

9-331  
1973

Form Approved.  
Budget Bureau No 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
Bedford, Inc.  
3. ADDRESS OF OPERATOR  
P.O. Box 255, Farmington, N.M. 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1450' fnl 1450' fel  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☒

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☒

(other) ☐

5. LEASE  
✓ SF081100-A  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A  
7. UNIT AGREEMENT NAME  
N/A  
8. FARM OR LEASE NAME  
✓ Ram  
9. WELL NO.  
✓ 1-A  
10. FIELD OR WILDCAT NAME  
WAW Fruitland - P.C.  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
✓ S8-T26N-R12W, N.M.P.M.  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mex.  
14. API NO.  
30-045-23339  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5966 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Propose moving on pulling unit, installing mastervalue, pressure testing 2 7/8" casing, swabbing hole to 1000', rig stripper head and perforate casing with 1 SPF from 1190-1197'. Acidize perfs with 250 gal. mud acid. If productive will run 1 1/4" tbg. with packer above perfs and complete natural. If non-productive, will Plug & Abandoned by filling existing 2 7/8" to surface with Class B cement, & erect dry-hole marker & clean, level & seed location in accordance with Federal regulations. Work to commence approximately August 14, 1979.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_

TITLE Agent

DATE August 9, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

NMOCC

\*See Instructions on Reverse Side

